



DISC	REV	MODEL	H.P.	VOLTS	CYC.	PHASE	R.P.M.	ROT	BEARINGS	THERMOSTAT	C	BA	F	BX	N	ALTER. SHAFT	WIDTH	THICK	LENGTH	CONN.	TYPE *	CHARACTERISTICS	REMARKS	NOTICE
DISC	001	608541-1	1/4	115	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	15/16	1/2	2	3/4	3/4	9/16					U.C.	BLOWER		
DISC	002	608541-2	1/3	115	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	3/16	1/2	2	3/4	7/8	9/16					U.C.	BLOWER		
DISC	003	608541-3	1/2	115	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	10/16	1/2	2	3/4	7/8	9/16					U.C.	BLOWER		
DISC	004	608541-4	3/4	115	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	1/16	1/2	3/4	7/8	9/16						U.C.	BLOWER		
DISC	005	608541-5	1	115	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	9/16	1/2	3/4	3/8	9/16						U.C.	BLOWER	U.L. APPROVED	
DISC	006	608542-1	1/4	115	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	15/16	1/2	3/4	3/4	9/16						U.C.	BLOWER	U.L. APPROVED	
DISC	007	608542-2	1/3	115	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	3/16	1/2	3/4	7/8	9/16						U.C.	BLOWER	U.L. APPROVED	
DISC	008	608542-3	1/2	115	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	10/16	1/2	3/4	7/8	9/16						U.C.	BLOWER	U.L. APPROVED	
DISC	009	608542-4	3/4	115	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	1/16	1/2	3/4	7/8	9/16						U.C.	BLOWER	U.L. APPROVED	
DISC	010	608542-5	1	115	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	9/16	1/2	3/4	3/8	9/16						U.C.	BLOWER		
DISC	011	608543-1	1/4	115	60	3Ø	3450	DUAL	SHIELDED BALL	MANUAL	15/16	1/2	3/4	3/4	9/16						U.C.	BLOWER		
DISC	012	608543-2	1/3	115	60	3Ø	3450	DUAL	SHIELDED BALL	MANUAL	3/16	1/2	3/4	7/8	9/16						U.C.	BLOWER		
DISC	013	608543-3	1/2	115	60	3Ø	3450	DUAL	SHIELDED BALL	MANUAL	10/16	1/2	3/4	7/8	9/16						U.C.	BLOWER		
DISC	014	608543-4	3/4	115	60	3Ø	3450	DUAL	SHIELDED BALL	MANUAL	1/16	1/2	3/4	7/8	9/16						U.C.	BLOWER		
DISC	015	608543-5	1	115	60	3Ø	3450	DUAL	SHIELDED BALL	MANUAL	9/16	1/2	3/4	3/8	9/16						U.C.	BLOWER		
DISC	016	608558-1	1/4	230	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	15/16	1/2	3/4	3/4	9/16						U.P.	NEMA	U.L. APPROVED	
DISC	017	608558-2	1/3	230	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	10/16	1/2	3/4	7/8	9/16						U.P.	NEMA	U.L. APPROVED	
DISC	018	608558-3	1/2	230	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	1/16	1/2	3/4	7/8	9/16						U.P.	NEMA	U.L. APPROVED	
DISC	019	608558-4	3/4	230	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	1/16	1/2	3/4	7/8	9/16						U.P.	NEMA	U.L. APPROVED	
DISC	020	608558-5	1	230	60	3Ø	3450	DUAL	SHIELDED BALL	AUTO RESET	9/16	1/2	3/4	3/8	9/16						U.P.	NEMA	U.L. APPROVED	
DISC	021	608568-1	1/4	230	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	15/16	1/2	3/4	3/4	9/16						U.P.	NEMA		
DISC	022	608568-2	1/3	230	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	3/16	1/2	3/4	7/8	9/16						U.P.	NEMA		
DISC	023	608568-3	1/2	230	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	10/16	1/2	3/4	7/8	9/16						U.P.	NEMA		
DISC	024	608568-4	3/4	230	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	1/16	1/2	3/4	7/8	9/16						U.P.	NEMA		
DISC	025	608568-5	1	230	60	3Ø	3450	DUAL	SHIELDED BALL	NONE	9/16	1/2	3/4	3/8	9/16						U.P.	NEMA		

DRAWING REVISION: W 0152300, APPROVED BY: G. RODRIGUEZ, DATE: 09-13-2018

REVISION BY: G. RODRIGUEZ, DATE: 09-13-2018

REVISION: 09-13-2018

OTHERWISE SPECIFIED: REMOVE BURRS & BREAK SHARP EDGES .003/.015 1076/3611X45 CORNER FILLETS R.02 [L51] MACHINED SURFACES .125 INCH / 3.175 mm SHOWN IN [BRACKETS]

TOLERANCES UNLESS OTHERWISE SPECIFIED: DISC: INCH mm ANGLE: ±0.1 (±2.5) ±0.5 (±12.7) XXX ±0.005 (±0.127) XXXX ±0.0005 (±0.0127)

DRAWN BY: R. LEWIS, DATE: 09-28-1966, APPROVED BY: HAS, DATE: 09-30-1966

DESCRIPTION: OUTLINE

MATERIAL: PROCESS/FINISH

THIRD ANGLE PROJECTION

SIZE: DWG NO 10698-001, SHEET 1