Uncontrolled Copy 4 APPD TYPE FRAME P.ROJAS 04-13-2012 ALL DIMENSIONS SHOWN IN PARENTHESIS 0025369 04-13-2012 R.RASCON ARE REFERENCE DIMENSIONS. ALL OTHER CS J56 DIMENSIONS ARE TOLERANCED PER CHART UNLESS OTHERWISE SPECIFIED 11.07±.055 [281.2±1.40] (6.50) [(165.1)] 1.94±.034 [49.3±.86] (1.64)(41.7)(4.08) [(103.6)] (2.84) [(72.1)] (.06) [(1.5)] 45°±2° 45°±2° 1.88 [47.8] (.69)[(17.5)](8.37) [(212.6)] 1/2-14 NPSM-WITH CAP —3/16 X 3/16 X 1.38[35.1] LONG KEY -10-32UNF-2A THRU-BOLTS ON (6.75)[(171.4)](\$\psi 5.812)[(\$\psi 147.63)] .6250 .6245 -GASKETS UNDER 3.500 -3.469 -88.90 88.11 15.875 15.862 COVER FOR ENCL MOTORS ONLY  $\otimes$ CORD HOLE PLUG FOR ENCL MOTORS ONLY .09 THK SLINGER (.69)[2.3] (BY EMI) • [(17.5)](2.75)(.13) [(3.3)] [(69.8)] -MOUNTING SLOTS (3.00).34[8.6] X 1.22[31.0] [(76.2)](2.44)(2.44)(62.0)(62.0)(4.00)[(101.6)](6.50) $[(165.1)]^{-}$ (5.00)• = CRITICAL DIMENSION  $[(127.0)]^{-}$ UNLESS OTHERWISE SPECIFIED
DIM. TOLERANCES ARE AS FOLLOWS:

X XX XXX XXXX
INCH ±.1 ±.02 ±.005 ±.0005
mm ±0.5 ±0.13 ±0.013
ANG. ±.50 DEG
REMOVE BURRS & BREAK SHARP EDGES:
INCH .003-.015 mm 0.1-0.4
CORNER FILLETS TO:
INCH .020 mm 0.5
MACHINE SURFACES:
INCH 125 mm 3.2 GEOMETRIC CHARACTERISTICS & SYMBOLS

| FLATNESS
| STRAIGHTNESS ADRIAN DE LUNA 03-01-2011 REGAL REGAL-BELOIT CORPORATION STRAIGHTNESS

ANGULARITY

PERPENDICULARITY (SQUARENESS)

PARALLELISM
O ROUNDNESS (CIRCULARITY)
CYLINDRICITY
PROFILE OF ANY SURFACE
PROFILE OF ANY LINE
RUNOUT
TRUE POSITION
CONCENTRICITY
SYMMETRY
ASME Y14.5M SAMUEL JIMENEZ 03-01-2011 DESCRIPTION OUTLINE CONFIDENTIAL: THIS DRAWING AND ITS INFORMATION ARE THE EXCLUSIVE AND CONFIDENTIAL PROPERTY OF REGAL—BELOIT CORPORATION AND ARE NOT TO BE DISCLOSED, DUPLICATED, DISTRIBUTED OR OTHERWISE USED WITHOUT THE WRITTEN CONSENT OF REGAL—BELOIT CORPORATION.

-ALL RIGHTS RESERVED. DWG NO C026 SHEET 1 ASME Y14.5M 1994 METRIC DIMS. SHOWN IN [BRACKETS] 4

Uncontrolled Copy 4 REVISION: ECO REVISADO POR: FECHA: APROBADO POR: FECHA: TIPO CARCAZA P.ROJAS 0025369 04-13-2012 R.RASCON 04-13-2012 TODAS LAS DIMENSIONES MOSTRADAS EN PARENTESIS SON DIMENSIONES DE REFERENCIA. TODAS LA DEMAS DIMENSIONES TIENEN TOLERANCIAS DE ACUERDO A LA TABLA A MENOS QUE SE ESPECIFIQUE OTRA COSA CS J56 11.07±.055 [281.2±1.40] (6.50) [(165.1)] 1.94±.034 [49.3±.86] (1.64)[(41.7)](2.84) [(72.1)] (4.08)[(103.6)] (.06) [(1.5)] 45°±2° 45°±2° [47.8] (.69)[(17.5)](8.37)ROSCA 1/2-14-NPSM CON TAPON [(212.6)]-3/16 X 3/16 X 1.38[35.1] LONGITUD CUÑA -10-32UNF-2A PERNOS PASADOS EN (6.75)[(171.4)](ø5.812)[(ø147.63)] ÈNTRE CENTROS .6250 .6245 -EMPAQUES BAJO 3.500 \_3.469 15.875 15.862 CUBIERTA PARA 88.90 88.11 MOTORES CERRADOS UNICAMENTE  $\otimes$ Œ -BARRENO PARA CLAVIJA UNICAMENTE PARA MOTORES .09 GROSOR DE ARANDELA CERRADOS [2.3] (POR EMI) [(17.5)] • (2.75)(.13) [(3.3)]  $[(69.8)]^{-}$ -RANURAS DE MOTAJE (3.00).34[8.6] X 1.22[31.0] [(76.2)](2.44)(2.44) $(62.0)^{-1}$ (62.0)(4.00)[(101.6)](6.50) $[(165.1)]^{-}$ (5.00)= DIMENSION CRITICA  $[(127.0)]^{-}$ DIBUJADO POR: ADRIAN DE LUNA 03-01-2011 REGAL REGAL-BELOIT CORPORATION APROBADO POR: SAMUEL JIMENEZ 03-01-2011 DESCRIPCION: FECHA EDS: REV. FORMATO: G TERCER ANGULO OUTLINE DE PROYECCION UIER SUPERFICIE
UIER LINEA

DEL BORDE.
PULG .003-.015 mm 0.1-0.4
FILETEAR ESQUINA: PULG .020 mm 0.5
MAQUINAR SUPERFICIES
PULG .125 mm 3.2

ASME Y14.5M 1994 DIMS METRICAS MOSTRADAS [PARENTESIS]

DEL BORDE.
PULG .003-.015 mm 0.1-0.4
SON PROPIEDAD DE USO EXCLUSIVO Y CONFIDENCIAL DE REGAL-BELOIT CORPORATION. Y NO DEBERAN SER REVELADOS, DUPLICADOS, DISTRIBUIDOS O USARSE DE OTRA MANERA SIN EL CONSENTIMIENTO ESCRITO DE REGAL-BELOIT CORPORATION. -TODOS LOS DERECHOS RESERVADOS.

DUPLICADOS, DISTRIBUIDOS O USARSE DE OTRA MANERA SIN EL CONSENTIMIENTO ESCRITO DE REGAL-BELOIT CORPORATION. -TODOS LOS DERECHOS RESERVADOS. NUMERO DE DIBUJO: . C026 ESCALA:NONE HOJA: 1 4

Uncontrolled Copy 4 P.ROJAS 04-13-2012 R.RASCON 04-13-2012 0025369 CS J56 11.07±.055 [281.2±1.40] (6.50) [(165.1)] 1.94±.034 [49.3±.86] (1.64) [(41.7)] (4.08) [(103.6)] (2.84) [(72.1)] (.06) [(1.5)] 45°±2° 45°±2° 1.88 [47.8] (.69) [(17.5)] (8.37) [(212.6)] (6.75) [(171.4)] .6250 .6245 15.875 15.862 3.500 3.469 88.90 88.11  $\otimes$ В .09 [2.3] (.69) [(17.5)] • (2.75) [(69.8)] (.13) [(3.3)] (3.00) [(76.2)] (2.44) [(62.0)] (2.44) [(62.0)] (4.00) [(101.6)] (6.50) [(165.1)] (5.00) [(127.0)] ADRIAN DE LUNA 03-01-2011 REGAL REGAL-BELOIT CORPORATION 03-01-2011 SAMUEL JIMENEZ 图纸格式版本 OUTLINE 机密:本图纸及相关信息所有权归REGAL-BELOIT CORPORATION。 未经REGAL-BELOIT CORPORATION书面授权,不得泄露、 C026 复制、传播或作其他用途。—版权所有 NONE ASME Y14.5M 1994 米制尺寸显示在[] 4