



- NOTES:  
 1) MAXIMUM FACE RUNOUT .004 T.I.R.  
 2) MAXIMUM PILOT ECCENTRICITY .004 T.I.R.  
 3) PERMISSIBLE SHAFT RUNOUT .002 T.I.R.  
 4) GASKETS THROUGHOUT.

DC127	13.81	11.75	8.99	180	3/4	1750
DC125	11.81	9.75	6.99	180	1/2	1750
DC115	13.81	11.75	8.99	90	3/4	1750
DC113	11.81	9.75	6.99	90	1/2	1750
CATALOG No.	"C"	"L"	"AD"	VOLTS	H.P.	RPM

				TOLERANCES UNLESS SPECIFIED				DRAWN SAD 8/9/2012	
				DEC INCHES				CHK	
				X ±.1		APPR			
01 ADDED 1.875 SHAFT DIM PER NEMA STANDARD, ADDED .06 & 1.94 REF DIMS. RELEASED TO PRODUCTION				IPG 9/14/12		XX ±.03		TITLE OUTLINE	
REF 027873, 612-0068, 46N3, DC113, DC115, DC125, DC127				SAD 8/9/2012		XXX ±.005		42 FRAME DC	
NO REVISION				BY & DATE		XXXX ±.0005		MATL	
						±1/2°		FINISH	
THIRD ANGLE PROJECTION						RFP		PREV	
						NETWORK FILE NAME 612-0075		SIZE B	
								DRAWING NO 612-0075	
								REV 01	