



- NOTES:
- 1) MAXIMUM FACE RUNOUT .004 T.I.R.
  - 2) PERMISSIBLE SHAFT RUNOUT .004 T.I.R.
  - 3) GASKETS THROUGHOUT.
  - 4) DRAIN HOLES PLUGGED AT 3, 9 AND 12 O'CLOCK. HOLES AT 6 O'CLOCK ARE OPEN (BOTH ENDS)

DC157	15.60	12.02	11.42	95	1	950
DC156	14.10	10.52	9.92	95	1/2	950
CATALOG No.	"C"	"L"	"AD"	VOLTS	HP	RPM

		TOLERANCES UNLESS SPECIFIED				DRAWN IPG 11/30/12			
		DEC.	INCHES			CHK			
		.X	$\pm$ .1	TITLE		APPD			
01	2.06 DIM WAS 2.18; OVERALL MOTOR LENGTH REDUCED BY .05"; RELEASED TO PRODUCTION	IPG	1/17/13	.XX	$\pm$ .03	SCALE	5=8		
00	RELEASED: REF. 612-0085 & D211	IPG	11/30/12	.XXX	$\pm$ .005	REF	612-0085		
NO.	REVISION	BY & DATE	CHK	ANG	$\pm$ 1/2'	FINISH	PREV		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	612-0109	SIZE	DRAWING NO.	REV.
				DIST			B	612-0109	01



OUTLINE  
42 FRAME DC