Uncontrolled Copy 4 REV BY APPD DATE ECO T.CUI 05-30-2012 B.SHEN 05-30-2012 0026448 ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS. ALL PERFORMANCE CURVE NO. MODEL NO. OTHER DIMENSIONS ARE TOLERANCED PER THE FOLLOWING CHART UNLESS C26090 H1040 OTHERWISE SPECIFIED. OVERALL DIM. = +/- .055= +/- .034SHAFT EXT. LEAD LENGTHS **EXTENDED** THRU-BOLTS = +/- .050ANGULAR DIM. $= +/- 2^{\circ}$ - 12.19 - (6.49) **--** 1.94 **--**-- (1.88) -- GASKET UNDER BRACKET COVER -(45)(45)(.06) 3/16 X 3/16 - X 1.38 LONG $\hat{\boldsymbol{\varnothing}}$ KEY 1/2-14 NPSM WITH CAP 00 (6.75).6250 .6245 3.500 3.469 (6.12)0 **SLINGER –** (.13) 4 MTG SLOTS **⊷** (.88) (.34 X 1.22) #10-32 THRU-BOLTS (2.75)(6.50)(3.00)ON A (5.812) DIA. B.C. (4.00)UNLESS OTHERWISE SPECIFIED
DIM. TOLERANCES ARE AS FOLLOWS:

X XX XXX XXXX
INCH ±.1 ±.02 ±.005 ±.0005
mm ±0.5 ±0.13 ±0.013
ANG. ±.50 DEG
REMOVE BURRS & BREAK SHARP EDGES:
INCH .003-.015 mm 0.1-0.4
CORNER FILLETS TO:
INCH 020 mm 0.5 GEOMETRIC CHARACTERISTICS & SYMBOLS

| FLATNESS
| STRAIGHTNESS 12-07-2004 REGAL REGAL-BELOIT CORPORATION STRAIGHTNESS

∠ ANGULARITY

L PERPENDICULARITY (SQUARENESS)

// PARALLELISM
O ROUNDNESS (CIRCULARITY)
// CYLINDRICITY

△ PROFILE OF ANY SURFACE
○ PROFILE OF ANY LINE
/ RUNOUT
◆ TRUE POSITION
⑥ CONCENTRICITY
- SYMMETRY

ASME, Y14.5M 12-07-2004 jshroa DESCRIPTION THIRD ANGLE PROJECTION (B) | EDS DATE 11-11-2011 | FORMAT REV H _____ OUTLINE CONFIDENTIAL: THIS DRAWING AND ITS INFORMATION ARE THE EXCLUSIVE AND CONFIDENTIAL PROPERTY OF REGAL—BELOIT CORPORATION AND ARE NOT TO BE DISCLOSED, DUPLICATED, DISTRIBUTED OR OTHERWISE USED WITHOUT THE WRITTEN CONSENT OF REGAL—BELOIT CORPORATION.

-ALL RIGHTS RESERVED. 0056 BB ENCL INCH .020 mm 0.5 MACHINE SURFACES: INCH 125 mm 3.2 DWG NO 18960501-001 SHEET 1 ASME Y14.5M 1994 METRIC DIMS. SHOWN IN [BRACKETS] 4

Uncontrolled Copy 4 REVISION: ECO REVISADO POR: FECHA: APROBADO POR: FECHA: 0026448 T.CUI 05-30-2012 B.SHEN 05-30-2012 ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS. ALL PERFORMANCE CURVE NO. MODEL NO. OTHER DIMENSIONS ARE TOLERANCED PER THE FOLLOWING CHART UNLESS H1040 C26090 OTHERWISE SPECIFIED. OVERALL DIM. = +/- .055= +/- .034SHAFT EXT. LEAD LENGTHS **EXTENDED** THRU-BOLTS = +/- .050ANGULAR DIM. $= +/- 2^{\circ}$ - 12.19 - (6.49) **--** 1.94 **--**-- (1.88) -- GASKET UNDER BRACKET COVER -(45)(45)(.06) 3/16 X 3/16 - X 1.38 LONG $\hat{\boldsymbol{\varnothing}}$ KEY 1/2-14 NPSM WITH CAP 00 (6.75).6250 .6245 3.500 3.469 (6.12)0 **SLINGER –** (.13) 4 MTG SLOTS **(**88.) — (.34 X 1.22) #10-32 THRU-BOLTS (2.75)(6.50)(3.00)ON A (5.812) DIA. B.C. (4.00)CARACTERISTICAS DE GEOMETRIA Y SIMBOLOS

7 PLANICIDAD

— RECTITUD

ANGULARIDAD

— PERPENDICULARIDAD (A ESCUADRA)

7 PARALELISMO

O REDONDEZ (CIRCULARIDAD)

CILINDRICIDAD

— PERFIL DE CUALQUIER SUPERFICIE

PERFIL DE CUALQUIER LINEA

7 VARIACION

POSICION REAL

CONCENTRICIDAD

— SIMBOLOS

A MENOS QUE SE ESPECIFIQUE DE

OTRA MANERA, LAS TOLERANCIAS DE

LAS DIMS; SON LAS SIGUIENTES:

X XX XXX XXXX

XXX XXX XXXX

PULG ±.1 ±.02 ±.005 ±.0005

mm ±0.5 ±0.13 ±0.013

ANG. ±.50 GRADOS

ELIMINAR REBABAS Y ORILLAS FILOSAS

DEL BORDE.

PULG .003-.015 mm 0.1-0.4

FILETEAR ESQUINA: PULG .020 mm 0.5

MAQUINAR SUPERFICIES

PULG 125 mm 3.2/

CONCENTRICIDAD

SIMBTENIA

ON DIMS METRICAS MOSTRADAS [PARENTESIS] DIBUJADO POR: dholt 12-07-2004 REGAL REGAL-BELOIT CORPORATION APROBADO POR: 12-07-2004 jshroa DESCRIPCION: FECHA EDS: 11-11-2011
REV. FORMATO: H TERCER ANGULO // PARALELISMO
O REDONDEZ (CIRCULARIDAD)
// CILINDRICIDAD
PERFIL DE CUALQUIER SUPERFICIE
PERFIL DE CUALQUIER LINEA
/ VARIACION
POSICION REAL
CONCENTRICIDAD
SIMETRIA
ASME Y14.5M 19 OUTLINE DE PROYECCION 0056 BB ENCL DEL BORDE.
PULG .003-.015 mm 0.1-0.4
FILETER ESQUINA: PULG .020 mm 0.5
MAQUINAR SUPERFICIES
PULG .125 mm 3.2

ASME Y14.5M 1994 DIMS METRICAS MOSTRADAS [PARENTESIS]

DEL BORDE.
CONFIDENCIAL: ESTE DIBUJO Y SU INFORMACION
SON PROPIEDAD DE USO EXCLUSIVO Y CONFIDENCIAL DE TAMAÑO:
DUPLICADOS, DISTRIBUIDOS O USARSE DE OTRA MANERA SIN EL CONSENTIMIENTO ESCRITO DE REGAL-BELOIT
CORPORATION. -TODOS LOS DERECHOS RESERVADOS. NUMERO DE DIBUJO: 18960501-001 ESCALA:NONE HOJA: 1 4

Uncontrolled Copy 4 编制 批准 ECO T.CUI 0026448 05-30-2012 B.SHEN 05-30-2012 ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS. ALL MODEL NO. PERFORMANCE CURVE NO. OTHER DIMENSIONS ARE TOLERANCED PER THE FOLLOWING CHART UNLESS H1040 C26090 OTHERWISE SPECIFIED. = +/- .055OVERALL DIM. = +/- .034SHAFT EXT. LEAD LENGTHS EXTENDED = +/- .050THRU-BOLTS $= +/- 2^{\circ}$ ANGULAR DIM. - 12.19 - (6.49) **-** 1.94 **-**- (1.88) - GASKET UNDER BRACKET COVER -(45)(45)(.06) 3/16 X 3/16 - X 1.38 LONG $\hat{\boldsymbol{\varnothing}}$ KEY 1/2-14 NPSM WITH CAP 00 (6.75).6250 .6245 3.500 3.469 (6.12)SLINGER — (.13) 4 MTG SLOTS **--** (.88) (.34 X 1.22) #10-32 THRU-BOLTS (2.75) -(6.50)(3.00) -ON A (5.812) DIA. B.C. (4.00)除另有注明 尺寸公差如下: dholt 12-07-2004 英寸 ±.1 ±.02 ±.005 ±.0005 毫米 ±0.5 ±0.13 ±0.013 角度 ±.50 度 清理毛刺和尖梭 蓝寸 000 015 REGAL**REGAL-BELOIT CORPORATION** jshroa 12-07-2004 -|图纸格式发布日期 11-11-2011| | 图纸格式版本 H OUTLINE 第三角投影 英寸 . 003-. 015 毫米 0. 1-0. 4 0056 BB ENCL 央寸 .003-.015 電水 0.1 内圆角 英寸 .020 毫米 0.5 表面粗糙度 英制 125 米制 3.2 机密:本图纸及相关信息所有权归REGAL-BELOIT CORPORATION 未经REGAL-BELOIT CORPORATION书面授权,不得泄露、 18960501-001 ◆ 位置度 ● 同轴度 - 对称度 复制、传播或作其他用途。--版权所有 NONE ASME Y14.5M 1994 米制尺寸显示在[] 4