



NAMEPLATE DATA		EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: MODEL CUST PN: CUST-PN: HP: HP SF: SF ROT: ROT RPM: RPM TYPE: TYPE CODE: CODE FORM: FORM FRAME: FRAME VOLTS: VOLTS AMPS: AMPS MAX AMPS: MAX-AMPS SF AMPS: SF-AMPS PH: PH HZ: HZ INS: INS AMB: AMB DUTY: DUTY ENCLOSURE: ENCLOSURE THERMALLY-PROTECTED		<p>183040-24</p> <p>LOW VOLTAGE</p> <p>4-BROWN 5-ORANGE 6-BLACK 1-RED 7-PURPLE 2-WHITE 8-GRAY 3-BLUE 9-PINK</p> <p>TO REVERSE, INTER-CHANGE ANY TWO LINE LEADS.</p> <p>HIGH VOLTAGE</p> <p>4-BROWN 7-PURPLE 5-ORANGE 8-GRAY 6-BLACK 9-PINK 1-RED 2-WHITE 3-BLUE</p> <p>LINE 1 LINE 2 LINE 3</p>	<p>1. PILOT DIAMETER IS CONCENTRIC WITH SHAFT CENTERLINE WITHIN .004 T.I.R.</p> <p>2. FACE OF MOUNTING FLANGE IS PERPENDICULAR TO SHAFT CENTERLINE WITHIN .004 T.I.R.</p> <p>3. SHAFT RUNOUT NOT TO EXCEED .002 T.I.R.</p> <p>4. END PLAY NOT TO EXCEED .010 MEASURED WITH NO THRUST</p> <p>5. ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS</p>

PERFORMANCE CURVE	APPROVED SAMPLE		
PERFORMANCE-CURVE	APPROVED-SAMPLE		
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
FILE#	CCN#	FILE#	GUIDE#
CUSTOMER	CUSTOMER		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY:
G	P.ROJAS	04-26-2019	DEC. INCH mm ANGLE	KHR
ECO	APPROVED BY	DATE	.XX ±0.1 [±2.5] ±0.5°	DATE:
ECO-0165900	P.ROJAS	04-26-2019	.XX ±0.02 [±0.51]	08-29-2005
ECO DESCRIPTION			.XXX ±0.005 [±0.127]	APPROVED BY:
SEE ECO			.XXXX ±0.0005 [±0.0127]	IDT
			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [.076/.381]	DATE:
			CORNER FILLETS .02 [.51]	07-29-2006
			MACHINED SURFACES 125/32	REFERENCE
			mm SHOWN IN [BRACKETS]	MATERIAL
				PROCESS/FINISH

REGAL™	Regal Beloit America, Inc.
DESCRIPTION: MODEL-CFHP-56FR OUTLINE	
SIZE	DWG NO: H741
THIRD ANGLE PROJECTION	SHEET 1