



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: F56AA77A01 CUST PN: HSQ1302 HP: 3.0 SF: 1.20 ROT: CW RPM: 3450 TYPE: CX CODE: N FORM: KJM FRAME: Y 56 Y VOLTS: 208-230 AMPS: 15.4 MAX AMPS: SF AMPS: PH: 1 HZ: 60 INS: F AMB: 60°C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED		<ol style="list-style-type: none"> FOR THREADED SHAFT EXT. ECCENTRICITY OF THREADED PORTION OF FOR THREADED SHAFT EXT. ECCENTRICITY OF THREADED PORTION OF ON O.D. OF GROUND RING GAGE AS SHOWN. THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR. END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS. FINISH PAINT TO BE BLACK. GREEN GROUND SCREW LOCATED UNDER COVER TO BE INSTALLED WITH A .09[2.3] MIN. GAP FOR EASY CONNECTION.

PERFORMANCE CURVE	APPROVED SAMPLE		
0116788	F56AA46A04		
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
E25022	XEWR2	LR4642	4211-01
CUSTOMER	DISTRIBUTION		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED
C	P.ROJAS	04-29-2019	DEC. INCH mm ANGLE
ECO	APPROVED BY	DATE	.X ±0.1 [±2.5] ±0.5°
ECO-0165900	P.ROJAS	04-29-2019	.XX ±0.02 [±0.51]
ECO DESCRIPTION			.XXX ±0.005 [±0.127]
SEE ECO			.XXXX ±0.0005 [±0.0127]
			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.076/.381] X 45° CORNER FILLETS R.02 [R.51]
			MACHINED SURFACES 125/3.2 INCH/mm
			mm SHOWN IN [BRACKETS]

DRAWN BY:	DATE:	APPROVED BY:	DATE:	REFERENCE:	THIRD ANGLE PROJECTION	SIZE	DWG NO	SHEET
CHERRY.ZHANG	07-14-2011	HONG.ZHU	07-14-2011		AS SHOWN	C	HSQ1302	1
Regal Beloit America, Inc.		DESCRIPTION MODEL-PFHP-56FR OUTLINE		MATERIAL PROCESS/FINISH				