



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: P48L2DA1 CUST PN: K3102 HP: 1 SF: 1.4 ROT: REVERSIBLE RPM: 3450 TYPE: P CODE: M FORM: FRAME: 56C VOLTS: 208-230/460 AMPS: 3.2/1.6 MAX AMPS: 4.0/2.0 SF AMPS: - PH: 3 HZ: 60 INS: B AMB: 40 DUTY: CONT ENCLOSURE: ODP -		(1) FINISH PAINT TO BE SATIN BLACK. (2) .438[11.13] WRENCH FLATS ON SHAFT -FOR ACCESS TO THIS WRENCH FLAT REMOVE END COVER. (3) CARBON STEEL SHAFT. (4) LIMITS ON AMPLITUDE OF VIBRATION MEASURED AT BEARING HOUSING = .001[.03]. (5) MAX. END PLAY LESS THAN .005[.13].

PERFORMANCE CURVE	APPROVED SAMPLE		
P48L2W1			
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
E46412	PRGY2	LR43341	4211-01
CUSTOMER	DISTRIBUTION SERVICES		

DRAWING REVISION C	REVISION BY P.ROJAS	DATE 04-29-2019	TOLERANCES UNLESS OTHERWISE SPECIFIED DEC. INCH mm ANGLE .XX ±0.1 [±2.5] ±0.5° .XX ±0.02 [±0.511] .XXX ±0.005 [±0.127] .XXXX ±0.0005 [±0.0127]	DRAWN BY: DZ	Regal Beloit America, Inc. DESCRIPTION MODEL-RFHP-48FR OUTLINE MATERIAL PROCESS/FINISH SIZE DWG NO K3102 SHEET 1
ECO ECO-0165900	APPROVED BY P.ROJAS	DATE 04-29-2019	REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.076/.381] X 45° CORNER FILLETS R.02 [5.1] MACHINED SURFACES 125/INCH 3.2/mm SHOWN IN [BRACKETS]	APPROVED BY: BS	
ECO DESCRIPTION SEE ECO				DATE: 10-21-2010	
				REFERENCE	