



NAMEPLATE DATA		EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: C48K2FC4A2 CUST PN: R1072ES HP: 3/4 SF: 1.65 ROT: CCWPE RPM: 3450 TYPE: C CODE: L FORM: FRAME: 48Y VOLTS: 230/115 AMPS: MAX AMPS: 7.4/14.8 SF AMPS: - PH: 1 HZ: 60 INS: B AMB: 40 DUTY: CONT. ENCLOSURE: ODP THERMALLY PROTECTED		<p>GRD GREEN (ROUND)</p> <p>HIGH VOLTAGE SHOWN. ROTATE DIAL CCW TO 115 FOR LOW VOLTAGE.</p> <p>USE COPPER CONDUCTORS ONLY. INSTALL MOTOR WITH VENTS DOWN.</p> <p>NEUTRAL LINE</p> <p>ACCEPTABLE FOR FIELD WIRING</p>	<ol style="list-style-type: none"> FINISH PAINT TO BE SATIN BLACK. .44[11.1] WRENCH FLATS ON SHAFT FOR ACCESS TO THIS WRENCH FLAT REMOVE END COVER. STAINLESS STEEL SHAFT EXT. LIMITS ON AMPLITUDE OF VIBRATION MEASURED AT BEARING HOUSING=.001[.03] CONNECT MOTOR FOR 115 VOLTS. QUICK VOLTAGE CHANGE PLUG INCLUDED ON TERMINAL BOARD. VOLT STICKER TO READ THAT CONNECTED VOLTAGE. MOTOR ASSEMBLY REF:624650-001

PERFORMANCE CURVE	APPROVED SAMPLE		
C48K2W26			
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
		LR43341	4211-01
CUSTOMER	DISTRIBUTION SERVICES		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY:	REGAL™ Regal Beloit America, Inc.	
C	F.NAVARRO	09-27-2016	DEC. INCH mm ANGLE	DZ		
ECO	APPROVED BY	DATE	.XX ±0.1 [±2.5] ±0.5°	DATE:	DESCRIPTION	
ECO-0109446	-	-	.XX ±0.02 [±0.51]	10-15-2010		MODEL-PFHP-48FR
ECO DESCRIPTION	SEE ECO		.XXX ±0.005 [±0.127]	APPROVED BY:	OUTLINE	
			.XXXX ±0.0005 [±0.0127]	BS		
<small>COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. (OWNER) AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.</small>			REMOVE BURRS & BREAK SHARP EDGES .003[.015] [0.076/.381] CORNER FILLETS .02 [51] MACHINED SURFACES $\frac{125}{\sqrt{mm}}$ INCH $\frac{3.2}{\sqrt{mm}}$ mm SHOWN IN [BRACKETS]	DATE: 10-15-2010 REFERENCE:	MATERIAL: _____ PROCESS/FINISH: _____	
				THIRD ANGLE PROJECTION	SIZE DWG NO	SHEET
					C R1072ES	1