



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: C48L2PA105C4 CUST PN: SQ1102 HP: 1.0 SF: 1.65 ROT: CCWPE RPM: 3450 TYPE: UAC FORM: CODE: N FRAME: 48Y VOLTS: 230/115 AMPS: MAX AMPS: 9.6/19.2 SF AMPS: 18.0/9.0 PH: 1 HZ: 60 INS: B AMB: 50C DUTY: CONT ENCLOSURE: ODP THERMALLY-PROTECTED		<ol style="list-style-type: none"> FINISH PAINT TO BE SATIN BLACK. .44 [11.2] WRENCH FLATS ON SHAFT-FOR ACCESS TO THIS WRENCH FLAT REMOVE END COVER. STAINLESS STEEL SHAFT EXT. LIMITS ON AMPLITUDE OF VIBRATION MEASURED AT BEARING HOUSING = .001 [0.02] CONNECTED FOR 230 VOLTS. QUICK VOLTAGE CHANGE DIAL INCLUDED ON THE TERMINAL BOARD. SUPPORT PAD TO BE PACKED WITH EACH MOTOR

PERFORMANCE CURVE	APPROVED SAMPLE		
C48L2W27			
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
E46412	PRGY2	LR43341	4211-01
CUSTOMER	DISTRIBUTION SERVICES		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY:	Regal Beloit America, Inc.
K			DEC. INCH mm ANGLE	JLG	
ECO	APPROVED BY	DATE	.X ±0.1 [±2.5] ±0.5°	DATE: 05-12-09	
ECO-0165900			.XX ±0.02 [±0.51]	APPROVED BY:	DESCRIPTION
SEE ECO			.XXX ±0.005 [±0.127]	DATE:	MODEL-PFHP-48FR
			.XXXX ±0.0005 [±0.0127]	REFERENCE	OUTLINE
COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.076/.381] CORNER FILLETS .02 [0.51] MACHINED SURFACES 125 INCH mm 3/2 mm SHOWN IN [BRACKETS]	MATERIAL SIZE DWG NO SQ1102	PROCESS/FINISH SHEET 1