



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: C48L2N134C1 CUST PN: UST1152 HP: 1 1/2 SF: 1.0 ROT: CCWPE RPM: 3450 TYPE: UAC CODE: H FORM: FRAME: 56J VOLTS: 230/115 AMPS: MAX_AMPS: 9.3/18.6 SF_AMPS: - PH: 1 HZ: 60 INS: B AMB: 50 DUTY: CONT ENCLOSURE: ODP THERM. PROT. CET40ABM		<ol style="list-style-type: none"> 1. FINISH PAINT TO BE SATIN BLACK. 2. .44[11.1] WRENCH FLATS ON SHAFT-FOR ACCESS TO THIS WRENCH FLAT REMOVE END COVER. 3. STAINLESS STEEL SHAFT EXT. 4. LIMITS ON AMPLITUDE OF VIBRATION MEASURED AT BEARING HOUSING = .001[.03]. 5. DUAL VOLTAGE MOTORS ARE TO BE CONNECTED FOR HIGHER VOLTAGE. QUICK VOLTAGE CHANGE PLUG INCLUDED ON THE TERMINAL BOARD. 6. SUPPORT PAD TO BE PACKED WITH EACH MOTOR

PERFORMANCE CURVE	APPROVED SAMPLE		
C48L2W36			
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
E46412	PRGY2	LR43341	4211-02
CUSTOMER	DISTRIBUTION SERVICES		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY:
K	M.RODARTE	05-01-2019	DEC. INCH mm ANGLE	JACK.Z
ECO	APPROVED BY	DATE	.X ±0.1 [±0.5] ±0.5°	DATE:
ECO-0165900	-	-	.XX ±0.02 [±0.13]	10-27-2009
ECO DESCRIPTION			.XXX ±0.005 [±0.013]	APPROVED BY:
SEE ECO			.XXXX ±0.0005 [±0.0013]	KG
			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [Ø8/38]	DATE:
			CORNER FILLETS .02 [5]	10-27-2009
			MACHINED SURFACES 125/INCH 3.2/mm	REFERENCE
			mm SHOWN IN [BRACKETS]	-

REGAL	Regal Beloit America, Inc.
DESCRIPTION	MODEL-PFHP-48FR OUTLINE
MATERIAL	PROCESS/FINISH
SIZE DWG NO	UST1152
SHEET	1