



NOTES:  
 1. MOTOR HAS #416 STAINLESS STEEL SHAFTING.  
 2. NO PACKING TAPE OVER CARTON LABEL.

CUSTOMER PN: D0307	ENVIRONMENT: DAMP
CUSTOMER: FASCO DISTRIBUTION	APPLICATION: COUNTER SALES
	MOTOR WEIGHT: -

CUSTOMER APPROVAL	FRONT SHAFT POSITION	MOTOR TYPE	REFERENCE SAMPLE
	HORIZONTAL	SHADED POLE	X-0006280-2
SIGNED:	DATE:	ORACLE REV B	
		DRAWING REVISION B	
		ECO-0058442	
		SEE ECO	

TYPICAL PERFORMANCE AT 115 VOLTS 60HZ.											
MOTOR SPEED	IDLE			LOADED			LOCKED			BREAK	
	RPM	AMP	WATT	IN OZ	RPM	AMP	WATT	IN OZ	AMP	WATT	IN OZ
1718	.99	59	22.6	1550	1.15	82	10.4	1.66	113	25.6	

ORACLE REV B	DATE 08-25-2014	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY: N.HONG
DRAWING REVISION B	DATE 08-25-2014	DEC. INCH mm ANGLE	DATE: 08-04-2014
ECO-0058442	APPROVED BY D.HUANG	.X ±0.1 (±2.5) ±0.5	APPROVED BY: H.ZHU
SEE ECO		.XX ±0.02 (±0.81)	DATE: 08-04-2014
		.XXX ±0.005 (±0.127)	PROCESS/FINISH: BLACK PAINT
		.XXXX ±0.0005 (±0.0127)	MATERIAL: -
		REMOVE BURRS & BREAK SHARP EDGES .003(.015 1.076(.381) CORNER FILLETS .02 (1.51) MACHINED SURFACES .125/32 INCH/mm 3/32 INCH/mm SHOWN IN [BRACKETS]	THIRD ANGLE PROJECTION

0046-4537 0046-4282

**FASCO** Fasco Industries, Inc. Motor Division

**SAFETY WARNING**

Assembled in Mexico

No. 71732155 TYPE U73B1 T.P. A0

115 V 60 Hz Class B

1.15 A 1550 RPM

Model D0307 E40513

Reference 1/25 HP

Max Amb 40°C

This Motor Must Be Grounded in Accordance With Local Or National Electrical Codes To Prevent Possible Injury Due To Electrical Shock

61299553

**REGAL** Regal Beloit America, Inc.

DESCRIPTION: MODEL-SFHP-3.3 OUTLINE

SIZE DWG NO: 71732155

SHEET 1-2