



LEAD MATERIAL
18 GA. 125°C. 2/64 INSUL.
X-LINKED POLYETHYLENE
(2) BLACK, 13.00/11.00 IN.
W/STRIP .56/.44 IN.

GROUND LEAD
GRN/YEL, 13.00/11.00 IN.
W/RING TERM. 8902 0157
AMP 350436-2

NOTES:
MOTOR HAS 416 S.S. SHAFT.
NO PACKAGING TAPE OVER CARTON LABEL.

0046 4537 0046 4282

FASCO Fasco Industries Inc. Motor Division

Assembled in Mexico

No. 71732156 TYPE U73B1 AO

115 V 60 Hz Class B

0.9 A 1550 RPM 1/40 HP

Model D0314 E40513

Thermally Protected

Max. Amb. 40°C

SAFETY WARNING

This Motor Must Be Grounded in Accordance With Local Or National Electrical Codes To Prevent Possible Injury Due To Electrical Shock

6129 9553

FRONT SHAFT POSITION	TYPICAL PERFORMANCE AT 120 VOLTS 60 Hz.												CUSTOMER: FASCO DIST.	FASCO MOTORS GROUP AC MOTOR/BLOWER DIVISION									
	MOTOR SPEED	IDLE			LOADED			LOCKED			BREAK	PART NUMBER: D0314				APPLICATION: COUNTER SALES							
R.P.M.		AMP.	WATT	IN.OZ.	R.P.M.	AMP.	WATT	IN.OZ.	AMP.	WATT	IN.OZ.												
HORIZONTAL DOWN	1750	.81	46	16.0	1550	.90	67	9.4	1.32	94	19.5	MOTOR WEIGHT:	MOTOR TYPE		DRAWING NUMBER								
													ENVIRONMENT: DAMP	SHADED POLE		7173 2156							
CUSTOMER APPROVAL:												FINISH COLOR: BLACK	B	LA	FR	A	S	C	E	B	A	REV.	
SIGNED:												DRAWN BY: S. DALTON	00	73	30	V	03	OP	5	3	0	00	
DATE:												DATE DRAWN: 3/10/2014											