


LEAD MATERIAL
18 GA. 125°C. 2/64 INSUL.
X-LINKED POLYETHYLENE
(2) BLACK, 14.00/12.00 IN.
W/STRIP .56/.44 IN.

GROUND LEAD
GRN/YEL, 14.00/12.00 IN.
W/RING TERM. 8902 0157
AMP 350436-2



0046 4537

0046 4282

FASCO Fasco Industries Inc. Motor Division Assembled in Mexico No. 71732154 TYPE U73B1 115 V 60 Hz 1.71 A 1550 RPM Model D031 Thermally Protected Reference 1/25 HP Max. Amb. 40°C		SAFETY WARNING This Motor Must Be Grounded in Accordance With Local Or National Electrical Codes To Prevent Possible Injury Due To Electrical Shock	
			AO Class B
			E40513

6129 9553

NOTES:
MOTOR HAS 416 STAINLESS STEEL SHAFT.
NO PACKAGING TAPE OVER CARTON LABEL.

FRONT SHAFT POSITION	TYPICAL PERFORMANCE AT 115 VOLTS 60 Hz.												CUSTOMER: FASCO DIST.	PART NUMBER: D031	FASCO MOTORS GROUP AC MOTOR/BLOWER DIVISION																																																									
	MOTOR SPEED	IDLE			LOADED			LOCKED			BREAK	APPLICATION:					MOTOR TYPE					DRAWING NUMBER																																																		
		R.P.M.	AMP.	WATT	IN.OZ.	R.P.M.	AMP.	WATT	IN.OZ.	AMP.	WATT	IN.OZ.		ENVIRONMENT: DRY					FINISH COLOR: BLACK					DRAWN BY: S. DALTON					DATE DRAWN: 2/26/2014					MOTOR TYPE					DRAWING NUMBER																																	
HORIZONTAL DOWN	1750	1.42	80	36.6	1550	1.70	124	18.1	2.51	172	18.1																																																													
CUSTOMER APPROVAL:																																																																								
SIGNED:																																																																								
DATE:																																																																								

FASCO FASCO MOTORS GROUP
AC MOTOR/BLOWER DIVISION

CONFIDENTIAL: DO NOT DUPLICATE OR DISCLOSE TO THIRD PARTIES WITHOUT WRITTEN PERMISSION OF FASCO MOTORS GROUP, AC MOTOR/BLOWER DIVISION.

SHADED POLE **7173 2154**

B	LA	FR	A	S	C	E	B	A	REV.
00	73	30	V	05	OJ	5	3	0	00

If Printed, this is an Uncontrolled Document.