



LEAD MATERIAL
18 GA. 125°C. 2/64 INS.
CROSS-LINKED POLYETHYLENE
WHITE, BLACK, RED,
11.00/9.00[279.40/228.60] TO END OF TERM.
HOUSING AMP #1-480305-0
WITH .084 PIN TERM. AMP #61118-1

GROUND LEAD
11.00/9.00[279.40/228.60] WITH SERRATED RING TERM.
TO FIT A #10 STUD AMP #350436-2

SAFETY WARNING
This motor must be grounded in accordance with local or national electrical codes to prevent possible injury due to electrical shock

AVERTISSEMENT DE SÉCURITÉ
Ce moteur doit être fondée sur conformément à la réglementation locale ou national électrique codes pour prévenir d'éventuelles blessures en raison de choc électrique

APPLY IN A CONVENIENT LOCATION TO READ FROM CLIP END

FASCO Motor Division

Assembled in Mexico
No. 71732375 TYPE U73SB1 T.P. A0
115 V 60 Hz Class B
.6/1.3 A 1050/1550 RPM
Model D0343 E40513
Reference 1/40 HP TWO-SPEED
Max Amb 40°C

Connection Diagram
Wht — Common
Blk — High
Red — Low
Grn/Yel — Grd

61299553

CUSTOMER PN:	D0343	ENVIRONMENT:	DAMP
CUSTOMER:	FASCO FDC	APPLICATION:	COUNTER SALES
		MOTOR WEIGHT:	-

CUSTOMER APPROVAL	FRONT SHAFT POSITION	MOTOR TYPE	REFERENCE SAMPLE NUMBER
	HORIZONTAL	SHADED POLE	X-0006639-4

SIGNED:	DATE:	TYPICAL PERFORMANCE AT 115 VOLTS 60 HZ									
		IDLE		FULL LOAD				LOCKED		BREAK	
MOTOR SPEED	RPM	AMP	WATT	IN OZ	RPM	AMP	WATT	IN OZ	AMP	WATT	IN OZ
HIGH	1734	1.23	82	15.7	1550	1.28	101	11.1	1.72	147	22.6
LOW	1725	.42	27	7.9	1050	.57	45	4.4	.63	50	8.7

ORACLE REV.	00A	DATE	02-02-2015
DRAWING REVISION	REVISION BY	DATE	DATE
A	N.HONG	02-02-2015	02-02-2015
ECO	APPROVED BY		
ECO-0069966	H.ZHU		
ECO DESCRIPTION			
SEE ECO			

DRAWN BY:	N.HONG	DATE:	02-02-2015
APPROVED BY:	H.ZHU	DATE:	02-02-2015
REFERENCE			
DESCRIPTION	MODEL-SFHP-3.3 OUTLINE		
MATERIAL		PROCESS/FINISH	BLACK PAINT
SIZE DWG NO	C	71732375	SHEET 1 OF 2

COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED.
PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. (OWNER) AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.

TOLERANCES UNLESS OTHERWISE SPECIFIED
DEC. INCH mm ANGLE
X ±0.1 [±2.5] ±0.5°
.XX ±0.02 [±0.51]
.XXX ±0.005 [±0.127]
.XXXX ±0.0005 [±0.0127]
REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.076/381]
CORNER FILLETS .02 [1.51]
MACHINED SURFACES $\sqrt{125}$ INCH $\sqrt{3.2}$ mm
mm SHOWN IN [BRACKETS]