



LEAD MATERIAL
18 GA. 125°C 2/64 INSUL.
X-LINKED POLY, (2) BLACK,
21.5/19.5[546.1/495.3] LONG
.56/.44[14.22/11.18] STRIP

GROUND LEAD MATERIAL
18 GA. 105°C 2/64 INSUL.
PVC, GRN/YEL LEAD
8.00/6.00[203.20/152.40] LONG
W/RING TERM. 8902-0157
AMP 350436-2

- NOTES:**
- MOTOR HAS 416 S.S. SHAFT.
 - NO PACKAGING TAPE OVER CARTON LABEL.

CUSTOMER PN: D0562	ENVIRONMENT: DAMP
CUSTOMER: FASCO DIST.	APPLICATION: COUNTER SALES
	MOTOR WEIGHT: -

SIGNED:	FRONT SHAFT POSITION UP HORIZONTAL DOWN	MOTOR TYPE					REFERENCE SAMPLE NUMBER				
		SHADED POLE					X-0006718-2				
DATE:		B	LA	FR	A	S	C	E	B	A	
		00	73	30	1	05	0J	5	3	0	

MOTOR SPEED	TYPICAL PERFORMANCE AT 115 VOLTS 50/60 HZ				FULL LOAD				LOCKED		BREAK
	RPM	AMP	WATT	IN OZ	RPM	AMP	WATT	IN OZ	AMP	WATT	IN OZ
115V 60Hz	1771	1.4	74	28	1630	1.5	107	14	2.4	165	38.6
115V 50Hz	1469	1.7	89	20	1400	1.8	109	20	2.9	209	51.5

ORACLE REV. 00E	DATE 02-11-2015	TOLERANCES UNLESS OTHERWISE SPECIFIED
DRAWING REVISION E	REVISION BY M.GU	DEC. INCH mm ANGLE
ECO-0070283	APPROVED BY C.ZHANG	.XX ±0.02 [±0.51] ±0.5°
SEE ECO		.XXX ±0.005 [±0.127]
		.XXXX ±0.0005 [±0.0127]
		REMOVE BURRS & BREAK SHARP EDGES .003/015 [0.076/381]
		CORNER FILLETS .02 [1.51]
		MACHINED SURFACES .125/ mm 3/2
		mm SHOWN IN [BRACKETS]

DRAWN BY: M.GU	DESCRIPTION: MODEL-SFHP-3.3
DATE: 07-09-2014	MATERIAL: BLACK PAINT
APPROVED BY: A.SUN	PROCESS/FINISH: BLACK PAINT
DATE: 07-09-2014	REFERENCE:
THIRD ANGLE PROJECTION	SIZE DWG NO: 71732244
	SHEET: 1 OF 2