



LEAD MATERIAL
18 GA. 125°C 2/64 INSUL.
X-LINKED POLY, (2) BLACK,
12.00/10.00 IN. LONG
.81/.69 IN. STRIP

- NOTES:
1. PACK 405 MOTORS MAX. PER PALLET.
 2. NO PACKAGING TAPE OVER CARTON LABEL.
 3. MOTOR HAS #416 STAINLESS STEEL SHAFTING.

0046-4072	0046-4282
Fasco Industries, Inc. Motor Division	
SAFETY WARNING	
This Motor Must Be Grounded in Accordance With Local Or National Electrical Codes To Prevent Possible Injury Due To Electrical Shock	
6129 9553	

FRONT SHAFT POSITION	TYPICAL PERFORMANCE AT 115 VOLTS 60 Hz.												CUSTOMER:	FASCO MOTORS GROUP AC MOTOR/BLOWER DIVISION																													
HORIZONTAL DOWN	MOTOR SPEED	IDLE			LOADED			LOCKED			BREAK	PART NUMBER:	CONFIDENTIAL: DO NOT DUPLICATE OR DISCLOSE TO THIRD PARTIES WITHOUT WRITTEN PERMISSION OF FASCO MOTORS GROUP, AC MOTOR/BLOWER DIVISION.																														
		R.P.M.	AMP.	WATT	IN.OZ.	R.P.M.	AMP.	WATT	IN.OZ.	AMP.	WATT	IN.OZ.											APPLICATION:																				
		1715	.38	23	7.45	1250	.47	36	4.34	.55	42	7.33	DIST.	MOTOR TYPE: SHADED POLE DRAWING NUMBER: 7173 1720																													
CUSTOMER APPROVAL:													ENVIRONMENT:	FINISH COLOR: BLACK																													
SIGNED:													DRAWN BY:	DATE DRAWN: 4-15-2005																													
DATE:														<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>B</td><td>LA</td><td>FR</td><td>A</td><td>S</td><td>C</td><td>E</td><td>B</td><td>A</td><td>REV.</td> </tr> <tr> <td>00</td><td>73</td><td>30</td><td>V</td><td>03</td><td>MR</td><td>5</td><td>1</td><td>0</td><td>01</td> </tr> </table>										B	LA	FR	A	S	C	E	B	A	REV.	00	73	30	V	03	MR	5	1	0	01
B	LA	FR	A	S	C	E	B	A	REV.																																		
00	73	30	V	03	MR	5	1	0	01																																		

If Printed, this is an Uncontrolled Document.