



LEAD MATERIAL
18 GA. 125°C 2/64 INSUL.
X-LINKED POLY, (2) BLACK,
14.00/12.00 IN. LONG
(1) W/ FSPADE TERM. 89039008
AMP# 42660-2
(1) W/ RING TERM. 89039009
AMP# 40955

0046-4072	Fasco Industries, Inc. Motor Division Assembled in Mexico No. 71637876 TYPE U63B1 T.P. AO LR6319 240 V 50/60 Hz Class B 0.4 A 1300/1550 RPM 1/90 HP Model D1119 Oil with SAE 20 Max Amb: 40°C	0046-4282
SAFETY WARNING This Motor Must Be Grounded in Accordance With Local Or National Electrical Codes To Prevent Possible Injury Due To Electrical Shock		

NOTES:
1. NO PACKING TAPE OVER CARTON LABEL.

FRONT SHAFT POSITION	TYPICAL PERFORMANCE AT 240 VOLTS 50 Hz.												CUSTOMER: FASCO DIST.	FASCO MOTORS GROUP AC MOTOR/BLOWER DIVISION										
HORIZONTAL 	MOTOR SPEED	IDLE			LOADED			LOCKED			BREAK	PART NUMBER: D1119	CONFIDENTIAL: DO NOT DUPLICATE OR DISCLOSE TO THIRD PARTIES WITHOUT WRITTEN PERMISSION OF FASCO MOTORS GROUP, AC MOTOR/BLOWER DIVISION.											
		R.P.M.	AMP.	WATT	IN.OZ.	R.P.M.	AMP.	WATT	IN.OZ.	AMP.	WATT	IN.OZ.	APPLICATION:	MOTOR TYPE			DRAWING NUMBER							
CUSTOMER APPROVAL:	50 Hz	1426	.34	44	10.1	1300	.35	53	6.5	.47	81	17.0	MOTOR WEIGHT: 2.00 POUNDS	SHADED POLE			7163 7876							
SIGNED:													ENVIRONMENT: DRY	B	LA	FR	A	S	C	E	B	A	REV.	
DATE:													FINISH COLOR: BLACK	00	63	30	V	01	HE	5	1	0	09	
													DRAWN BY: TAMMY JONES											
													DATE DRAWN: MARCH 6, 2002											

If Printed, this is an Uncontrolled Document.