



LEAD MATERIAL  
18 GA. 3/64 INS. 105°C. SPT-2  
BLACK, WITH 125 V PLUG PER NEMA 1-15P.

- NOTES:
- MOTOR HAS #416 S.S. SHAFING.
  - NO PACKAGING TAPE OVER CARTON LABEL.

6130 5568

**SAFETY WARNING**  
This motor must be grounded in accordance with local or national electrical codes to prevent possible injury due to electrical shock

**AVERTISSEMENT DE SÉCURITÉ**  
Ce moteur doit être fondée sur conformément à la réglementation locale ou national électrique codes pour prévenir d'éventuelles blessures en raison de choc électrique

00464668

**FASCO** Fasco Industrles, Inc.  
Motor Division

Assembled in Mexico

No. 71732209 TYPE U73B1 T.P. A0  
120 V 60 Hz Class B  
1.0 A 1625 RPM 1/45 HP  
Model D632 E40513  
Max Amb 40°C

APPLY IN A CONVENIENT LOCATION TO READ FROM CLIP END

CUSTOMER PN:	D632	ENVIRONMENT:	DAMP
CUSTOMER:	FASCO DIST	APPLICATION:	COUNTER SALES
		MOTOR WEIGHT:	-

SIGNED:	FRONT SHAFT POSITION	MOTOR TYPE										REFERENCE SAMPLE NUMBER				
		SHADED POLE										X-0006587-2				
DATE:	HORIZONTAL	B	LA	FR	A	S	C	E	B	A						
	DOWN	00	73	30	V	01	EM	5	1	0						

TYPICAL PERFORMANCE AT		120 VOLTS				60 HZ					
MOTOR SPEED	IDLE		FULL LOAD				LOCKED		BREAK		
	RPM	AMP	WATT	IN OZ	RPM	AMP	WATT	IN OZ	AMP	WATT	
	1759	0.98	57	13.3	1625	1.01	73	7.7	1.48	119	22.5

ORACLE REV.	OOC	DATE	02-13-2015
DRAWING REVISION	REVISION BY	DATE	02-14-2015
ECO	H.ZHU	DATE	02-14-2015
ECO-0070283	D.HUANG		
ECO DESCRIPTION			
SEE ECO			

DRAWN BY:	A.SUN	DATE:	05-16-2014
APPROVED BY:	A.SUN	DATE:	05-16-2014
REFERENCE			
THIRD ANGLE PROJECTION			

**REGAL** Regal Beloit America, Inc.

DESCRIPTION: MODEL-SFHP-3.3

MATERIAL: PROCESS/FINISH: BLACK PAINT

SIZE DWG NO: 71732209

SHEET: 1-2

D  
C  
B  
A

D  
C  
B  
A

4 3 2 1

4 3 2 1

4 3 2 1

4 3 2 1