



NOTES:
1. MOTOR HAS 416 S.S. SHAFT.
2. NO PACKAGING TAPE OVER CARTON LABEL.

6130 5568

SAFETY WARNING
This motor must be grounded in accordance with local or national electrical codes to prevent possible injury due to electrical shock

AVERTISSEMENT DE SÉCURITÉ
Ce moteur doit être fondée sur conformément à la réglementation locale ou national électrique codes pour prévenir d'éventuelles blessures en raison de choc électrique

APPLY IN A CONVENIENT LOCATION TO READ FROM CLIP END

00464537

Fasco Industries, Inc. Motor Division

Assembled in Mexico
No. 71732389 TYPE U73B1 T.P. A0
115 V 60 Hz Class B
1.0 A 1500 RPM
Model D9623 E40513
Reference .027HP SW280-1
CENT SWITCH 125VA-120V
Max Amb 40°C

00469183

Connection Diagram

Blk — Line
Blk — Line
Red — Line
Red — Line
Grn/Yel — Grd

CUSTOMER PN: D9623	ENVIRONMENT: DAMP
CUSTOMER: FASCO DIST.	APPLICATION: COUNTER SALES
	MOTOR WEIGHT: -

SIGNED:	FRONT SHAFT POSITION UP DOWN HORIZONTAL	MOTOR TYPE					REFERENCE SAMPLE NUMBER				
		SHADED POLE					X-0008383-1				
DATE:		B	LA	FR	A	S	C	E	B	A	
		00	73	34	F	03	DM	5	3	0	

TYPICAL PERFORMANCE AT 115V VOLTS 60 HZ		IDLE				FULL LOAD				LOCKED		BREAK
MOTOR SPEED	RPM	AMP	WATT	IN OZ	RPM	AMP	WATT	IN OZ	AMP	WATT	IN OZ	IN OZ
HIGH	1752	.85	48	16.8	1500	1.0	71	10.2	1.33	96	19.3	

ORACLE REV 00A	DATE 01-29-2015	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY: N.HONG
DRAWING REVISION A	DATE 01-29-2015	DEC. INCH mm ANGLE	DATE: 01-29-2015
ECO-0069827	APPROVED BY: D.HUANG	.XX ±0.02 (±0.51)	APPROVED BY: H.ZHU
ECO DESCRIPTION SEE ECO		.XXX ±0.005 (±0.127)	DATE: 01-29-2015
		.XXXX ±0.0005 (±0.0127)	REFERENCE
		REMOVE BURRS & BREAK SHARP EDGES .003/015 (0.076/381)	DESCRIPTION MODEL-SFHP-3.3 OUTLINE
		CORNER FILLETS .02 (1.51)	MATERIAL
		MACHINED SURFACES .125/3mm	PROCESS/FINISH BLACK PAINT
		mm SHOWN IN [BRACKETS]	SIZE DWG NO 71732389

THIRD ANGLE PROJECTION	REGAL Regal Beloit America, Inc.	SHEET 1-2
------------------------	----------------------------------	-----------