



LEAD MATERIAL:
18 GA. 125°C, 2/64 INSUL
X-LINKED POLY., (2) BLACK

- NOTES:
- SHAFT EXTENSION MEASURED WITH END PLAY PUSHED IN.
 - SHIM BOTH ENDS WITH (1) PC 246 WASHER AND (1) PC 247 WASHER. ADD PC 247 WASHER ON BACK END AS REQUIRED TO MAINTAIN SPECIFIED ENDPLAY.
 - MOTOR MUST START AT 70 VOLTS.
 - HIPOT PER 88834420.
 - ROTOR CORE, STATOR CORE AND STATOR BAR ASSEMBLIES ARE COATED WITH TWIN EMULSION.
 - FOLD PC 137 IN HALF AROUND CORD.
 - PACK 6 PER CONTAINER, 12 CONTAINERS PER LAYER, 9 LAYERS PER PALLET, 648 MAX. AMOUNT PER PALLET. PACKING ASSEMBLY 87854178, PER 88834200 AND 88834408.
 - CARTON LABELS MUST ALL FACE ON EDIRECTION TOWARD THE OPEN END OF THE PALLET. SEE 88834408.
 - NO PACKAGING TAPE OVER CARTON LABEL.

61305568

SAFETY WARNING
This motor must be grounded in accordance with local or national electrical codes to prevent possible injury due to electrical shock.



AVERTISSEMENT DE SECURITE
Ce moteur doit être fondée sur conformément à la réglementation locale ou national électrique codes pour prévenir d'éventuelles blessures en raison de choc électrique

61299553

99581186

CUSTOMER:	FASCO DIST.	APPLICATION:										
CUSTOMER PN:	K110	MOTOR WEIGHT:	1.5 LBS									
	UP	ENVIRONMENT:	DRY									
HORIZONTAL	MOTOR TYPE					REFERENCE SAMPLE						
	B	LA	FR	A	S	C	E	B	A			
	00	58	52	X	12	OH	5	A	0			
TYPICAL PERFORMANCE AT 115 VOLTS 60 HZ												
	IDLE			LOADED			LOCKED			BREAK		
MOTOR SPEED	RPM	AMP	WATT	IN OZ	RPM	AMP	WATT	IN OZ	AMP	WATT	IN OZ	
	3455	.70	31	4.74	3000	.77	.41	3.24	.95	50	6.25	

DRAWING REVISION EA	REVISION BY JMG	DATE 02/05/2018	TOLERANCES UNLESS OTHERWISE SPECIFIED: DEC. INCH mm ANGLE X ±0.1 [±2.5] s1° .XX ±0.01 [±0.25] .XXX ±0.005 [±0.127] .XXXX ±0.0005 [±0.0127]	DRAWN BY RPT	DATE 02/24/2015
ECO-0140321	APPROVED BY PLA	DATE 02/05/2018	REMOVE BURRS & BREAK SHARP EDGES: .003 [.015] [0.76] [38.1] X 45° CORNER FILLETS: R.02 [51] MACHINED SURFACES: .125 /mm 3.2 /mm SHOWN IN [BRACKETS]	APPROVED BY ML	DATE 02/24/2015
ECO DESCRIPTION REDRAWN TO SW. REVISE CORD.			THIRD ANGLE PROJECTION	DESCRIPTION OUTLINE MOTOR ASSY	MATERIAL
COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. FORNERY AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.			REGAL™ Regal Beloit America, Inc.	PROCESS/FINISH	DRAWING NUMBER 71581190
			SIZE C	DRAWING NUMBER 71581190	SHEET 1 OF 1