



NOTES:
1) GASKETS BETWEEN FRAME AND ENDBELLS, CONDUIT BOX AND FRAME, AND CONDUIT BOX COVER AND CONDUIT BOX.

SPEED RANGE RPM	FULL LOAD TORQUE LB.-IN.	INPUT HP	OVERHUNG LOAD LBS.	RATIO TO 1
250-4	50	1/4	235	10

		TOLERANCES UNLESS SPECIFIED		DAYTON® Dayton Electric Mfg. Co. Lake Forest IL 60045 USA	DRAWN	LST 2/17/10			
		DEC.	INCHES		CHK	APPD			
		.X	±.1	TITLE	SCALE	5-8			
02	REVISED GRAINGER ADDRESS AS PER IS12-2651	UD	9/12/12	PI	.XXX	±.005			
01	CORRECTED PLACING OF NAMEPLATE, ISAAC 10-3043	IPG	7/20/2010		.XXXX	±.0005			
NO.	REVISION	BY & DATE	CHK	ANG	±1/2'	FINISH			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	5CJD10D	SIZE	DRAWING NO.	REV.
				DIST			B	5CJD10D	02