



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90 ° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING 180 °.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	2FF	BS
1350	364T	13.24	28.64	11.25	---	5.63
1450	364/365T	14.24	29.64	11.25	12.25	6.13

		TOLERANCES UNLESS SPECIFIED				DRAWN JJB 10-02-2009	
		DEC	INCHES			CHK MH 10-02-2009	APPR MJS 10-02-2009
3	UPDATED FRAME ISAAC 09-5049 & ADDED F2 VIEW	EH	05-17-2012	MH	XX	±.03	TITLE OUTLINE
2	UPDATED FRAME, BRACKETS, & COND BOX CN24390	KL	03-28-2005		XXX	±.005	360T FR - TEAO/TENV - TAPPED LEAD HOLE
1	NEW DRAWING MU25005	KL	04-30-1999		XXXX	±.0005	MATL
NO		REVISION		BY & DATE		FINISH	
		THIRD ANGLE PROJECTION		CHK LANG ±7°30'		PREV	
				RFP NETWORK FILE NAME SS517119		PAGE OF	
				SIZE B		DRAWING NO SS517119	
						REV 3	