



- NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

(B-SS509469)



DRAWN TLB 02-04-1988
 CHK FG 02-04-1988
 APPR ML 02-04-1988

NO		REVISION		BY & DATE		TOLERANCES UNLESS SPECIFIED		TITLE		DRAWN	
NO		REVISION		BY & DATE		TOLERANCES UNLESS SPECIFIED		TITLE		DRAWN	
NO		REVISION		BY & DATE		TOLERANCES UNLESS SPECIFIED		TITLE		DRAWN	
8	MODELED IN SOLIDWORKS & ADDED F2 VIEW MU 97811	JJB	11/2/2010	X	±.1	DEC INCHES		OUTLINE		TLB	02-04-1988
7	UPDATED FRAME & CONDUIT BOX CN 24390	KL	4/4/2005	XX	±.03	DEC INCHES		360TSC FR. - DR. PR. - C'FACE		FG	02-04-1988
6	REDRAWN IN AUTOCAD	TAT	6/29/2004	ML	±.005	DEC INCHES		SCALE 1:4		ML	02-04-1988
5	REDRAWN ON CAD	TLB	2/4/1988	XXXX	±.0005	DEC INCHES		REF		FMF	
				CHK	ANG ±7°30'	DEC INCHES		FINISH		PAGE	OF
				THIRD ANGLE PROJECTION		RFP 02-04-1988		PREV		SIZE	DRAWING NO
						NETWORK FILE NAME SS508618				B	SS508618
											REV
											8

DASH	FRAME	B	C	AG	2F	BS
1400	364TSC	13.25	26.50	23.00	11.25	5.62
1500	365TSC	14.25	27.50	24.00	12.25	6.12