



DASH	FRAME	С	Α		
325	48Y	10.25	3.75		
375	48Y	10.75	4.25		
425	48Y	11.25	4.75		
450	48Y	11.50	5.00		
475	48Y	11.75	5.25		

LEAD DESCRIPTION:

1 WHITE, 1BLACK, BARE WIRE STRIPPED .50, 30.00" LONG

1 BROWN AND 1 BROWN WITH WHITE MARK WITH .25 FLAG TYPE QUICK CONNECT 30.00" LONG. BROWN LEAD WITH WHITE MARK IS COMMON TO WHITE.

PURPLE AND YELLOW REVERSING LEADS ARE MOLDED INTO MATING PULL APART PLUGS 5.00° LONG.

GREEN GROUND WITH TERM. FOR #10 SCREW 12.00" LONG.

	<i>-</i>		————LINE
MOTOR _	-GREEN - GRO		
	>PURPLE —	<u>.</u>	PURPLE
	YELLOW — PURPLE		PURPLE YELLOW
ROTATION:	CCW LEAD EN	D	CW LEAD END
		D A WAL	AD 12/20/00

	4/3	401	11./5	5.25	3.122.1 3.133.1 13.1 #13.2 #13.2 23.13.					ROTATION: CCW LEAD END			D CW LEAD END	
							TOL UNLES	ERANCES S SPECIFIED		ЪП		DRAWN	AD 12/2	9/09
							DEC.	INCHES		<u>ال ب</u>	لماك	CHK	NB 12/2	9/09
							.x	±.1				APPD	NB 12/2	9/09
							.xx	±.03	TITLE OUTLINE				3=8	1
							.xxx	±.005	1			REF	SS74406	3
							.xxxx	±.0005	MAT'L.			FMF		
NO.				REVISION	BY & DATE	снк	ANG	±7'30"	FINISH				PREV	
IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED				RFP			CAD FILE ss74406	SIZE	DRAWING NO			REV.		
				DIST	WP] A	SS	40389	4			