


NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90 ° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180 °
3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

REVISION		BY & DATE		TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC	DRAWN	
NO	DESCRIPTION	CHK	ANG	DEC	INCHES		CHK	DATE
5	REVISED FRAME AND DASH TABLE ISAAC09-5049	TJW	4/1/2010	EH	DEC	TITLE OUTLINE - TEBC - STD. 444/445TC.FR. MATL FINISH PREV NETWORK FILE NAME SSS15884	KL	1/8/1997
4	UPDATED DRAWING	RJW	5/7/2007	X	±.1		ML	1/9/1997
3	BLOWER MOTOR ROTATED 90° CBOX @ F3 CN224459	PGK	7/9/1997	XX	±.03		DJK	1/9/1997
2	REVISED TO SHOW FRAME WITH CAST-IN LUG CN22904	MH	2/25/1997	XXX	±.005		SCALE	1:8
1	NEW DRAWING MU12868	KL	1/9/1997	XXXX	±.0005		REF	
				±7.30"		FMF		
						PAGE	OF	

DASH	FRAME	B	C	AG	BS	2F	2XF
1825	444TC	17.75	52.85	44.60	7.25	14.50	---
2025	444/445TC	19.75	54.85	46.60	8.25	14.50	16.50

THIRD ANGLE PROJECTION



SIZE **B** DRAWING NO **SS515884** REV **5**