02 USEM pg 1	1 English																
VAR 001	MODEL P63AJJ-1349	CUSTOMER USEM	CAT. NO. D32P1ACR	A 11.89	В	C	D	HP	VOLTS 208-230/460	SF 1.15	AMPS 4.7-4.4/2.2	HZ 60	RPM	CONN VOLTS	PROT. NONE	DESCR	IPTION / REMARKS N56C, ODP
001	P63AJJ-1349	USEIVI	D32PTACK	11.89				1 1/2	208-230/460	1.15	4.7-4.4/2.2	60	3450		NONE		N30C, ODF
$\rightarrow$										+ -					<u> </u>		
+										+ -		1					
NIDEC I	MOTOR CORPORAT	THERMAL PRO (IF REQUIRED) (6.500)	ROUND SCRE DIECTOR  14 NPSM THRI H CONDUIT P	EAD —			NA VARNIN ABEL	MEPLA	TOP		T KEY TAPED OTOR		062 ±.031			4 HOLES 3/8-16 UNC-2 TAPED .750	2B THREAD
NIDEC MOTOR CORPORATION 21-Oct-15  REVISION RECORD FOR: E23969								TOLERANCES ON DIMENSIONS NIDEC MOTOR CORPORATION									
ADDFD /	CRITICAL REQ. #5 A					(1	UNLESS OTH	ERWISE SPE	IEIED)	RMATION D						NOT BE	REVISION DATE : 08-OCT-15
							INCHES .XX = ± .010	<u>m</u>	n RE	PRODUCED	SCLOSED ON THIS DOCU OR DISCLOSEDWITHOU	T WRITTEN	N CONSENT OF			TION	08-OCT-15
ISSUED BY	A. DEL ANG	ENGINEER A	W. GARZ				$XX = \pm .010$	i	CHE	TOM	ER DETAI	ו הם	2 // // // 1	G V		1TEM NO. 304559	REV SHEET DW SIZ A 1 OF 6 E