



CONNECTIONS

LOW VOLTAGE



HIGH VOLTAGE



C 2P DUAL VOLT

REV W/CAP & PROT



ROTATION:
CW SWITCH END REVERSIBLE
TO REVERSE ROTATION, INTERCHANGE
BLACK AND RED LEADS.

NOTE:
SECURE ALL LEADS AT 3:00 OCLOCK
LOCATION TO PREVENT INTERFERENCE
WITH MOVING PARTS.

REFER TO SEIM 24-1

NIDEC CONFIDENTIAL
NIDEC MOTOR CORPORATION 07-Oct-13

REVISION DESCRIPTION FOR: C8396-07 CHANGED FROM MICROSTATION TO SOLIDEDGE	SCALE: NONE UNITS: INCHES	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED) INCHES: ± .015 mm: mm	TITLE: DIAGRAM OF CONNECTIONS	NIDEC MOTOR CORPORATION
MATERIAL:	ISSUED BY: A. SANCHEZ	APPROVED BY: J.I. SALAZAR	REVISION DATE: 04-OCT-13	
MUST BE COMPLIANT TO RoHS DIRECTIVE EU 2002/95/IEC AND REGULATION EC 1907/2006 (REACH) AS AMENDED	CODE: D04	DWG NO.: 745167	REV: A	SHEET NUMBER: 1 OF 1 DWG SIZE: B