



FOR HIGH VOLTAGE:
 BRN TO P
 BLK TO 3
 WHT TO 3
 RED TO 5

L1 TO T1
 L2 TO T4

ROTATION: CW SWITCH END REVERSIBLE
 TO REVERSE ROTATION, INTERCHANGE BLACK AND RED LEADS

C 2P DUAL VOLT REV W/CAP & PROT

REV A

REFER TO SEIM 24-1

REVISION DESCRIPTION FOR: C8396-07	SCALE: NONE	UNITS: INCHES	TITLE: DIAGRAM OF CONNECTIONS		NIDEC MOTOR CORPORATION
CHANGED FROM MICROSTATION TO SOLIDEDGE	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED)		ISSUED BY: A. SANCHEZ		
MATERIAL:	INCHES: ± .015	mm	APPROVED BY: J.I. SALAZAR	REV: A	SHEET NUMBER: 1 OF 1
	ANGLES: ±		CODE: D04	DWG. NO.: 743785	DWG. SIZE: B

NIDEC CONFIDENTIAL
 NIDEC MOTOR CORPORATION 07-Oct-13

MUST BE COMPLIANT TO RoHS DIRECTIVE EU 2002/95/IEC AND REGULATION EC 1907/2006 (REACH) AS AMENDED