



CONNECTIONS

LOW VOLTAGE		HIGH VOLTAGE	
BLU	L1	BLU	L1
BRN	●	BRN	INSUL.
ORG		ORG	●
WHT	●	WHT	
YEL		L2	YEL

ROTATION:
CW SWITCH END.

NOTE:
SECURE ALL LEADS AT 3:00 OCLOCK
LOCATION TO PREVENT INTERFERENCE
WITH MOVING PARTS.

C 4P DUAL VOLT NON-REV W/CAP & PROT REV A
REFER TO SEIM 24-1

NIDEC CONFIDENTIAL
NIDEC MOTOR CORPORATION 24-Sep-13

REVISION DESCRIPTION FOR: C8396-08 UPDATED BACKGROUND TO NIDEC	SCALE: NONE UNITS: IN	TITLE: DIAGRAM OF CONNECTIONS	NIDEC MOTOR CORPORATION
MATERIAL:	TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED) INCHES: XX = ± .01 .XXX = ± .005 ANGLES X° = ± 1°	ISSUED BY: A. SANCHEZ APPROVED BY: J.I. SALAZAR	REVISION DATE: 24-SEP-13
MUST BE COMPLIANT TO ROHS DIRECTIVE EU 2002/95/IEC AND REGULATION EC 1907/2006 (REACH) AS AMENDED		CODE: D04 DWG NO.: 748059	REV: A SHEET NUMBER: 1 OF 1 DWG SIZE: B