



- FOR HIGH VOLTAGE:
- L1 ——— 1
  - BRN ——— P
  - RED ——— 3
  - WHT ——— 5
  - BLK ——— 2
  - L2 ——— 4

- FOR LOW VOLTAGE:
- L1 ——— 1
  - RED ——— 2
  - BRN ——— 3
  - BLK ——— 5
  - WHT ——— 4
  - L2 ——— 4

ROTATION: CCW SWITCH END REVERSIBLE  
TO REVERSE ROTATION, INTERCHANGE BLACK AND RED LEADS

C 2P DUAL VOLT REV W/CAP & PROT

REV A

NIDEC CONFIDENTIAL  
NIDEC MOTOR CORPORATION 24-Sep-13

REVISION DESCRIPTION FOR: C8396-10 CHANGED MARKUP EMERSON TO NIDEC.	SCALE NONE TOLERANCES ON DIMENSIONS (UNLESS OTHERWISE SPECIFIED) INCHES ± .015 mm ANGLES X° = ±1°	UNITS IN	TITLE <b>DIAGRAM OF CONNECTIONS</b>	NIDEC MOTOR CORPORATION
MATERIAL:	ISSUED BY J.G.SALINAS CODE D04	APPROVED BY J.I.SALAZAR	REVISION DATE 24-SEP-2013	REV A
MUST BE COMPLIANT TO RoHS DIRECTIVE EU 2002/95/IEC AND REGULATION EC 1907/2006 (REACH) AS AMENDED	DWG NO. 761121		SHEET NUMBER 1 OF 1	DWG SIZE B