


12 LEADS #18, .031 THICK INSUL TO EXTEND BEYOND MOTOR 6.000 +2 -0 MEASURING FROM INTERNAL CONNECTION BOX LEADS TO BE NUMBERED 1 THRU 12 AND SKINNED .750.



NIDEC MOTOR CORPORATION 14-Feb-12

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN	
P63SYFGD-4114		WHOLESALE-INDUSTRIAL	1	208-230/460 190/380	3.7/1.9	60/50	1140/950	REVERSIBLE	SV1EA3D	
SHEET NUMBER 1 OF 1	REV D	REVISION RECORD FOR: C4997-13 UPDATED BACKGROUND FROM EMERSON TO NIDEC			INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION				NIDEC MOTOR CORPORATION	
REVISION DATE 14-FEB-12										
ISSUED BY A. SANCHEZ	REVIEWED BY J.I. SALAZAR	ENGINEER APPROVED J.I. SALAZAR								
				TITLE ASSEMBLED VIEW				CODE V01	ITEM NO. 755121	SIZE A