



(6) LEADS 18, 2/64 THICK INSL. TO EXTEND BEYOND MOTOR INTO CONDUIT BOX  
 BLACK=6.000±1.000, RED=6.000±1.000,  
 BLUE=6.000±1.000, YELLOW=6.000±1.000  
 ORANGE=6.000±1.000, WHITE=6.000±1.000  
 LEADS TO BE SKINNED .750±.250

NIDEC MOTOR CORPORATION 17-Apr-12

| MODEL       | REF | CUSTOMER | HP  | VOLTS       | AMPS        | HZ | RPM  | ROTATION   | CUSTOMER PN |
|-------------|-----|----------|-----|-------------|-------------|----|------|------------|-------------|
| C55KGR-4925 |     | USEM     | 1/3 | 115/208-230 | 5.5/2.7-2.8 | 60 | 3450 | REVERSIBLE | T13C1J4     |

| SHEET NUMBER  | REV | REVISION RECORD FOR: C5431-00     |
|---------------|-----|-----------------------------------|
| 1 OF 1        | B   | CHANGED POSITION OF WARNING LABEL |
| REVISION DATE |     |                                   |
| 17-APR-12     |     |                                   |

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

**NIDEC MOTOR CORPORATION**

| ISSUED BY     | REVIEWED BY | ENGINEER APPROVED |
|---------------|-------------|-------------------|
| J. PATROCINIO | V. RIVERA   | V. RIVERA         |

| TITLE          | CODE | ITEM NO. | SIZE |
|----------------|------|----------|------|
| ASSEMBLED VIEW | V01  | 763572   | A    |