



ALL LEADS TO EXIT INTO CONDUIT BOX AND EXTEND BEYOND THE SHELL 6.000±1.000 & TO BE STRIPPED .750

1/2-14 NPT TYP WITH CONDUIT PLUG

375-16 UNC-2B .68 DEEP 4 NOS. EQUALLY SPACED

VAR	MODEL	CATALOG NO.	C	HP	VOLTS	HZ	RPM	BASE REQUIREMENT	PROTECTOR
001	C63JLH-5439	WD1C2JHC	13.815	1	115/208-230	60	1725	YES	NONE

SHEET NUMBER	REV	REVISION RECORD FOR:	C6906-00
1 OF 1	C	CHANGED POSITION OF WARNING LABEL AND NAMEPLATE	
REVISION DATE			
07-JAN-13			
ISSUED BY	REVIEWED BY	ENGINEER APPROVED	
A. SANCHEZ	V. RIVERA	B. CAMMACK	

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

**NIDEC MOTOR CORPORATION**

ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE IS GIVEN

TITLE  
**ASSEMBLED VIEW**

CODE  
**V01**

ITEM NO.  
**767628**

SIZE  
**B**