

Bona Craft Oil 2K Care

Technical data sheet

Bona Craft Oil 2k Care is a maintenance oil for previously oiled floors, designed to refresh the oils and restore its protective qualities. Bona Craft Oil 2k Care should be applied as needed based on floors appearance. Visit bona.com for additional product information.

- Restores look of oiled floor
- Very low VOC's
- Easy to apply
- Specifically designed for oiled floors

Technical data

Physical Characteristics:

Ingredients – Vegetable oil, oil-modified polyurethane resin, petroleum distillates, wax and driers

VOC's – 35 g/L (.30 pounds per gallon VOC)

Dry time – 12 hours (60-80 F and 35-75% relative humidity).

Applicators – Bona® Cut-In pad, Bona® steel trowel and Bona® Cotton Cloths or rubber bladed applicator.

Coverage rate – 600-1,200 sq. ft. per container

Shelf life – 2 years in unopened container

Disposal – Wastes and emptied containers should be handled in accordance with local regulations.

Packaging – 1.0-liter plastic container

Recommended Use

- Residential
- Commercial

Directions

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEETS.

FOR TECHNICAL ADVICE: Call Bona US at 800-872-5515

COMPATIBILITY: Bona Craft Oil 2K Care can be used on Bona Craft Oil 2K or any natural penetrating oil. Product results may vary widely. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.

BONA CRAFT OIL 2K CARE SYSTEM: Bona Craft Oil 2K Care is a maintenance oil for previously oiled floors, designed to refresh the oils and restore its protective qualities. Bona Craft Oil 2k Care should be applied as needed based on floors appearance. Visit bona.com for additional product information.

RECOMMENDED APPLICATORS: Red buffing pad, Bona Cut-in Pad, Bona Steel Trowel and Bona Cotton Cloths.

MIXING INSTRUCTIONS: SHAKE WELL BEFORE USING. DO NOT THIN. DO NOT ADD WATER.

APPLICATION: 1. Thoroughly clean floor using the Bona Deep Clean System or Bona Craft Oil 2K Soap following label directions. 2. Allow floor to dry completely. 3. Apply a thin coat of the Bona Craft Oil 2K Care to the floor using a 175 rpm buffer and a red buffing pad working back and forth with the grain of the wood when possible. For areas the buffer cannot reach, use a trowel or cut-in pad to apply. 4. Allow the oil to penetrate the wood surface for 15-30 minutes. 5. Remove excess oil using a buffer and a clean, Bona Cotton Cloth wrapped around a 1" white, red or green buffing pad. Change cotton cloth as needed. 6. Allow oil to dry thoroughly before use (12 hours under ideal conditions of 65-80 F and 40-60% relative humidity). High humidity and or low temperature conditions will extend dry time, while increased ventilation and airflow will reduce dry time. BE SURE YOU ARE USING THE RECOMMENDED COVERAGE OF APPROXIMATELY 600-1,200 SQ. FT. PER CONTAINER (coverage may vary dependent on condition of floor).

CLEAN-UP: Application tools should be cleaned with mineral spirits.

STABILITY: Two year shelf life in unopened container.

STORAGE: Store in a climate-controlled environment. KEEP FROM FREEZING. Do not store above 100° F.

DANGER: RAGS, STEEL WOOL OR WASTE SOAKED WITH BONA CRAFT OIL REFRESHER MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED, METAL CONTAINER.

Finishing



Bona Craft Oil 2K Care

Technical data sheet

Finishing



Order Information

Item #	Size	#/Case
GT525113020	1.0 Liter (33.8 oz.)	6