

SH 15 SL GB Set AX

SMALL WATER HEATERS 5 TO 15 L

PRODUCT-NO.: 227692

For installation above the draw-off point, the small water heater SH..SL is ideal, irrespective of whether you want to supply one or several draw-off points. These devices are available with capacities of 10 or 15 litres. They can be adjusted anywhere between 35 °C and 82 °C, making water with a consistent temperature available at all times. The thermal cut-out provides a permanent, safety-first maximum water temperature. This can be set to 38, 45, 55 or 65 °C. The highly effective thermal insulation of the small water heaters ensures the lowest energy losses.



The main features

Small water heater, 15 litre capacity

Low standby loss power consumption

For one or several draw-off points

Splashproof to IP 24 D

Economy setting 60 °C

Installation with the KV safety assembly

Power cable for permanent connection, approx. 1 m



Type	SH 10 SL GB Set AX	SH 10 SLi GB Set A	SH 15 SL GB Set AX	SH 10 SLi
Part no.	227690	227693	227692	229476
Connected load	2 kW	2 kW	3,3 kW	2 kW
Height	503 mm	503 mm	601 mm	503 mm
Width	295 mm	295 mm	316 mm	295 mm
Depth	275 mm	275 mm	295 mm	275 mm

Technical data

Rated capacity	10 l	10 l	15 l	10 l
Power supply	1/N/PE	1/N/PE	1/N/PE	1/N/PE
Rated voltage	230 V	230 V	230 V	230 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Standby energy consumption/24 h at 65 °C	0,34 kWh	0,34 kWh	0,4 kWh	0,34 kWh
Colour	white	white	white	white
IP-Rating	IP24	IP24	IP24	IP24
Energy efficiency class	A	A	A	A
Weight	8,1 kg	8,1 kg	11,1 kg	8 kg

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.