



glove@n Hammer

Nitrile Exam Gloves Powder Free, Standard Cuff

Hammer is the nitrile glove meant to deliver an impact for the tough jobs that demand high tensile strength, elongation and a definitive colour. This glove is suitable for security, tattooist, beauty salon, motor mechanic, cleaner and general maintenance.

NON STERRILE LATEX 2 CE UN BUILDING

	GloveOn Hammer	
Length (mm)		
	≥ 240	
Thickness Measurements (mm)		
Palm (centre of Palm)	0.08 ± 0.02	
Finger (13mm \pm 3mm from tip)	0.12 ± 0.02	
Physical Properties	Before Ageing	After Ageing
Tensile Strength (MPa)	≥ 18	≥ 16
Elongation (%)	≥ 500	≥ 500
Elongation after Isopropanol immersion (%)	≥ 500	N/A
Inspection Levels & AQL	Inspection Level	AQL
Watertightness	G1	1.50
Physical Dimensions	S2	4.00
Tensile Strength	S2	4.00
Visual Inspection (Major)	S4	2.50
Visual Inspection (Minor)	S4	4.00
Particulate Residue	N = 5	≤ 2mg/glove

REORDER CODE

GMN23SS	SMALL
GMN23MM	MEDIUM
GMN23LL	LARGE
GMN23XL	X-LARGE
GMN23XXL	XX-LARGE

FEATURES

- Fingertip textured
- Powder free
- Not made with natural rubber latex
- UL certified to meet NFPA 1999
- Ambidextrous
- Standard cuff
- Black colour

PACKAGING

100 gloves per box for S to L 90 gloves per box for XL 80 gloves per box for XXL 10 boxes per carton

REGULATORY COMPLIANCE

TGA - ARTG 164563, FDA 510(k), MDD 93/42/EEC, REACH, ROHS Directive 2002/95/EC

STANDARDS

ASTM D6319, ASTM D6978, EN455 part 1, 2, 3 & 4, NFPA 1999

MANUFACTURING ACCREDITATIONS

ISO 9001:2008 ISO 13485:2003 EN ISO 13485:2012



Your Medical Supply Solution

Abyvo Toll free: (800) 989-6697 cs@abyvo.com

