

# DPAK 3 + TAB BREAKOUT BOARD

(10 x 9.84, 2.54 mm)

SKU: ICB00180




## **Description**

This is a breakout board that was designed to be a DIP adapter for the DPAK 3 + tab (TO-263) type SMD packages. Some of the SMD types that can be used with this board include: D2PAK, DDPAK, DPAK, TO-252, SOT-428 and other TO and SOT types.

## **Technical Details**

Footprint Dimensions		
Body (mm):	10 x 9.84	
Pitch (mm):	2.54	
Thermal Pad (mm):	n/a	
Breakout Board Dimensions		
Board Dimensions (mil):	480 x 835	
Board Thickness (mil):	62	
Through-Hole Spacing (mil):	100 mil (X-axis)	
	n/a (Y-axis)	
Breakout Board Specifications		
Board Layers:	2	
Finish:	Immersion Gold	
Copper:	1 oz	
Traces (mil)	30	
Trace Lengths (mil):	<100	
Pin/Through-Hole Count:	5	



www.icbreakout.com | admin@icbreakout.com



#### What's Included?

Parts Installed on Board:	None
Parts Included	5 PIN Break Away Header
(but not installed):	(Straight)

#### **Additional Features**

- Easily identifiable PIN 1 indicator and PIN numbers
- White silk "Label Pads" allow you to label the pins for quick reference
- Extended through-hole pads make for an easy connection point for surface mount parts
- · Breadboard friendly pin spacing
- All boards have been E-tested for failures and are RoHS compliant

## **Scale Image**




1:1 SCALE


(Print this page to use the scale image to test the fit of the electronic part.)



### **Dimensions**



FOOTPRINT DIMENSIONS



BREAKOUT BOARD DIMENSIONS