



WWW.AISINTERFACE.COM

For TECH SUPPORT call 1-833-AIS-TECH



AUTOMOTIVE INTEGRATION SOLUTIONS

USBCD2

**USB CD PLAYER FOR
SELECT MAKES & MODELS**

Applications

Most vehicles that do not have a factory CD players.

For a complete list of vehicles that have been validated please go to www.automotiveintsolutions.com and click on the USBCD2.

Parts inside the box

CD unit x 1

USB extension x 1



IMPORTANT !!!

Due to the fact that there are over 7000 models vehicles produced with out CD players , the list of vehicles on our site is only what we have validated that this unit will work 100%. This does not mean that vehicles that are not on the list will not work.

Due to the recording process, Some CD's like library CD's and books on CD have copyright protection embedded in them and will not allow them to play in our unit. If the CD doesn't play, it is possible that it is copyright protected.

Some Vehicles for compatibility can not use the USB extension. See full list of compatible vehicles at www.aisinterface.com

TEST AND VALIDATE THE UNIT FIRST

To validate the unit, simply plug the USB into the factory USB port. Depending on the factory radio you may have to touch the media or USB icon or button.

The USB icon will not be active until a CD in put into the unit. Once you have inserted the CD, allow it to play for 15 seconds before touching the radio.

Allow the unit to play the CD for at least 5 to 10 minutes. Test your track back and forth and make sure the factory radio does not lock up. If the factory radio locks up, simply unplug the USBCD2 and cycle the vehicle off and on.

To reset the unit, a new CD has to inserted into the unit. The Table of contents is what resets the unit.

The USBCD2 can be mounted either at a 0 degrees or 90 degrees. It is not designed to be mounted at an angle other 0 or 90.

