

Dome 13W

Recessed Dimmable LED Downlight Luminaire

Energy efficient 13w IP44 recessed fixed LED downlight luminaire with an opal acrylic lens using high brightness Samsung SMD LEDs that allows high luminous efficacy with minimal energy consumption and excellent thermal performance.

Features

- Trim Ring – Matt white
- Lens - Opal Acrylic
- Light Source – Samsung SMD LED
- Colour Temperature – Available in 3000k and 4000k
- Beam Angle – 90° wide beam
- CRI - >80
- Lamp Life - 50,000 hrs average
- Passive cooling heat sink to maintain low LED operating temperatures
- Constant current LED driver remote with 1.2 metre flex and plug
- Power Factor – >0.9
- Dimmable



**Ceiling Cutout
90mm**

Product No.	System Power	Colour Temp	Dimensions	Luminous Flux	Luminaire Efficacy
CLD 580-013 - 3K	13W	3000k	110mm x 42mm	940 lm	72 lm/w
CLD 580-013 - 4K	13W	4000k	110mm x 42mm	980 lm	75 lm/w

Weight: 0.3kg

Applications

Ideal for both residential and commercial applications such as houses, apartments, lobbies, foyers, retail outlets, restaurants, etc

Installation Instructions

PLEASE READ THESE INSTRUCTIONS CAREFULLY BEFORE INSTALLATION OF THE PRODUCT

- Ensure power supply is disconnected at the mains before initiating installation of the Luminaire
- Cut out a 90mm diameter hole in the ceiling
- With the mains power turned off make the electrical connection to the LED driver and then pass the driver through the aperture, try to place the driver in a well ventilated area no less than 50mm from the luminaire.
- Connect the flying leads from the LED driver to the luminaire and then lift and hold the mounting springs on both sides of the luminaire and pass through the aperture
- With the springs now up in the void, gently allow the springs to release, the luminaire should then hold itself flush to the ceiling surface
- Please make sure that the working area is free from dust or other contaminants that can effect performance
- The luminaire should not be covered with any type of insulating material, there should be a minimum of 100mm of free space around the luminaire and 50mm of free space above the luminaire.
- Designed for indoor use only

IT IS RECOMMENDED THAT THESE LUMINAIRES BE INSTALLED AND FITTED BY A LICENSED ELECTRICIAN IN ACCORDANCE WITH CURRENT WIRING REGULATIONS

