



  
**Tuttnauer**

**EMBRACE YOUR CHOICES**  
TABLE TOP LINE AUTOCLAVES & ACCESSORIES

# EZPlus™ Series Fully Automatic

## EZGlide self locking door

Ergonomically friendly EZGlide door features effortless opening and closing with an automatic double safety locking mechanism. Glide the door closed with a gentle push to close and lock it.



## EZFill front water filling

Accessible front or top water filling options

## EZView multi-color display

For easy reading, even from a distance

Chamber Temp:	270.0 °F	Temperature	076.3 °F
Cycle Time:	4.0 min	Pressure	0.00 MPa
Log Time:	30 min		
System Ready			

## Capacity

Available in 9" and 11" chamber sizes

## Network port (rear located)

For connection to a local network to provide remote monitoring of the system

## Comprehensive warranty

2 year parts and labor and 10 year chamber warranty



## Standards and directives

Designed to meet the most current sterilization standards ANSI/AAMI ST55

## Closed door drying








Door remains closed *through* the entire dry cycle to maintain sterility and ensure efficient drying. High efficiency air pump circulates filtered air through the chamber for fast drying. 0.2µm HEPA air filter (replaceable).

## Dynamic air removal technology

Effectively removes air from the chamber

## Sterilization Programs

EZPlus is easy to operate with 4 FDA cleared sterilization programs. Additionally, there are 2 customizable sterilization programs, A and B\*\*. A convenient Chamber Brite cleaning program simplifies maintenance when utilizing Chamber Brite powdered autoclave cleaner.

Sterilization programs		Temp.	Hot Cycle Time (fill, heat up and vent)	Sterilization Time (minutes)	Dry Time* (minutes)	Total Hot Cycle Time (Without Dry)	Total Hot Cycle Time (With Dry)
Description	Icon						
Unwrapped Instruments		270°F	EZ9PLUS: 20min. EZ11PLUS: 24min.	3	1	EZ9PLUS: 23min. EZ11PLUS: 27min.	EZ9PLUS: 24min. EZ11PLUS: 28min.
Wrapped Instruments, Pouches		270°F	EZ9PLUS: 17min. EZ11PLUS: 21min.	4	30	EZ9PLUS: 21min. EZ11PLUS: 25min.	EZ9PLUS: 51min. EZ11PLUS: 55min.
Unwrapped Delicate Instruments		250°F	EZ9PLUS: 16min. EZ11PLUS: 19min.	30	1	EZ9PLUS: 46min. EZ11PLUS: 49min.	EZ9PLUS: 47min. EZ11PLUS: 50min.
Handpieces		270°F	EZ9PLUS: 21min. EZ11PLUS: 26min.	4	30	EZ9PLUS: 25min. EZ11PLUS: 30min.	EZ9PLUS: 55min. EZ11PLUS: 60min.
Chamber Brite Cleaning		270°F	EZ9PLUS: 17min. EZ11PLUS: 20min.	3(keep temperature)	N/A	EZ9PLUS: 20min. EZ11PLUS: 23min.	EZ9PLUS: N/A EZ11PLUS: N/A
Custom A**		270°F	EZ9PLUS: 20min. EZ11PLUS: 22min.	4	30	EZ9PLUS: 24min. EZ11PLUS: 26min.	EZ9PLUS: 54min. EZ11PLUS: 56min.
Custom B**		250°F	EZ9PLUS: 13min. EZ11PLUS: 16min.	30	1	EZ9PLUS: 43min. EZ11PLUS: 46min.	EZ9PLUS: 44min. EZ11PLUS: 47min.


\* Operator has the option to add additional drying time.

\*\* Custom A and Custom B programs are not FDA cleared. It is the user's responsibility to validate any Custom cycles.

NOTE: cycle times are approximate and may vary depending on instrument loads.



# EZPlus™ Series Fully Automatic Sterilizers



### Innovative EZView multi-color display

A bright, new LCD panel uses active multi-color display technology for easy reading, even from a distance

### EZPad

Consists of 3 keys, allowing the user to browse with ease through the sterilization programs and user directories

### Optional Printer

Documents detailed history of each cycle

### \*USB Port (located under door cover)

Store and transfer approximately 100 cycles of data

\*Includes USB flash drive with machine.


## Innovative EZView multi-color display

Real time information is easy to read, even from a distance.

Indicates program icon and name, cycle parameters, temperature and pressure in the chamber.

During the selected program each stage of the sterilization cycle is displayed with both an active color wheel and text.

- The color of the wheel and text change for each phase of the cycle
- Wheel moves to indicate activity through each part of the cycle
- Remaining time displayed during Water Filling, Sterilization, and Drying phases
- Display available in multiple languages



## Technical Specifications

Item No.	Chamber Dimensions Ø x L in (mm)	Volume	Overall Dimensions* DxWxH in (mm)	Standard Cassette Capacity **	Tray Dimensions DxWxH in (mm)	No. of Trays	Voltage (V) Freq. (Hz)	Power (W) Current (A)	Shipping Weight lbs (kg)
<b>EZ9Plus</b>	9"x19.8" (230x504)	5.2gal 19.8L	24.8"x19.1"x15.1"* (630x485x384)	2 Full & 2 Half** (loaded horizontally)	16.3"x6.7"x0.6" (413x169x16)	3	120V 50/60	1400W 12A	104(47)
<b>EZ11Plus</b>	11"x19.8" (280x504)	7.5gal 28.5L	24.8"x20.9"x17.3"* (630x530x440)	4 Full & 4 Half** (loaded vertically)	16.3"x6.7"x0.6" (413x169x16)	5	120V 50/60	1400W 12A	126 (57)

\* Models EZ9Plus and EZ11Plus require a minimum tabletop depth of 22".

\*\*Standard full size cassette is 8" x 11" and standard half size cassette is 8" x 5.5".

## Documentation

- Optional printer documents a detailed history of each cycle
- 100 cycles can be stored on the autoclave for reprinting or downloading to a PC
- USB port enables users to easily transfer cycle data via a flash drive to a PC
- Network port allows for connection to a local network for use with RPCR Software for remote monitoring
- Optional RPCR Software Generates a report that includes detailed specifications of the cycle including graphs and tables to measure specific parameters and data values, with an option to save the report in PDF file format. The RPCR feature can be operated in both online mode, via an Ethernet connection, and offline mode, via a USB device.

## Standards and Directives

**The EZPlus Series meets established international standards and specifications:**

USA Standards: ANSI/AAMI ST55:2010, ASME Sec. VIII, Div 1, UL 61010-1, UL 61010-2-040, FDA 510(K) Cleared, ISO 17665-1:2006. The Quality System complies with ISO 13485:2003 and ISO 9001:2008 Canada Standards: CMDR

**EU Standards:** EN 13060:2004 + A2:2010, EN 61010-1, EN 61010-2-040, EN 61326-1. Complying with MDD 93/42/EEC, PED 97/23/EC, RoHS & WEEE compliance, EN 60529 (IP31)



## Designed to meet the most current sterilization standards ANSI/AAMI ST55



EZ11Plus loaded with 4 full and 4 half cassettes.



EZ9Plus loaded with 2 full and 2 half cassettes.

# EZ9™ & EZ10™ Fully Automatic Sterilizers

Optional Printer



## Features:

- Closed door active drying system to maintain sterility and ensure efficient drying of packs and pouches.
- High efficiency air pump circulates hot air after the sterilization cycle for fast drying.
- Hepa filter 0.2µm air filter (replaceable).
- Pre-programmed cycles for: unwrapped instruments; wrapped/packs; glassware and additional drying cycle.
- All program parameters can be customized and stored.
- Automatic shut off at the end of both the sterilization and dry cycles.
- Audible and visual cycle interruption alert.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Low water sensor prevents activation of sterilization cycle when there is insufficient water in the chamber or reservoir.
- Constant monitoring of temperature and pressure for sterilization.
- Power outage recovery system.
- Door design prevents steam from coming in contact with control panel.

- Optional internal printer documents: date, time, temperature and pressure.
- 510k clearance for dental handpieces.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- International certifications.
- 2 year parts and labor warranty.
- 10 year chamber warranty

## Control Panel:



1. Program Selection
2. Detailed Digital Display
3. Programmable Keys
4. System Indicators

Item No.	Chamber Dimensions Ø x L In(mm)	Volume	Overall Dimensions DxWxH In(mm)	Standard Cassettes**	Tray Dimensions DxWxH In(mm)	No. of Trays	Standard Unwrapped Cycle time	Voltage(V) Freq.(Hz)	Power(W) Current(A)	Shipping Weight lbs(kg)
<b>EZ9™</b>	9" x 18" (230 x 470)	5gal/19L	21.5"x20"x14.4" (545x510x365)	2 full/2 half	16.3"x6.7"x0.8" (415x170x20)	3	Cold: 27 mins Hot: 13 mins	120V 50/60	1400W 12A	95 (43)
<b>EZ10™</b>	10" x 19" (254 x 475)	6gal/23L	21.5"x20"x14.4" (545x510x365)	3 full/3 half	16.3"x6.7"x0.8" (415x170x20)	4	Cold: 30 mins Hot: 14 mins	120V 50/60	1400W 12A	95 (43)

NOTE: cycle times are approximate and may vary depending on instrument loads. \*\*Standard full size cassette is 8" x 11" and standard half size cassette is 8" x 5.5".

## EZ10k™ Fully Automatic Sterilizer



1. Program Selection
2. Detailed Digital Display
3. Programmable Keys
4. System Indicators

### Fully Automatic Kwiklave™:

The Tuttnauer EZ series is also available in a quick cycle model, the Kwiklave (EZ10k). This sterilizer offers all the proven, dependable features of our fully automatic autoclaves, with the added benefit of reducing the total heat up time. This autoclave is the perfect choice for quick instrument turnaround or a high volume office. Speed and reliability are accomplished without sacrificing load size. 2 year parts and labor warranty. 10 year chamber warranty. **Model EZ10k requires a voltage between 220V and 235V for proper operation. When applicable a buck/boost transformer (0.5KVA) may be required.\***

Optional Printer



Item No.	Chamber Dimensions Ø x L In(mm)	Volume	Overall Dimensions DxWxH In(mm)	Standard Cassettes**	Tray Dimensions DxWxH In(mm)	No. of Trays	Standard Unwrapped Cycle time	Voltage(V) Freq.(Hz) *	Power(W) Current(A)	Shipping Weight lbs(kg)
<b>EZ10k™ Kwiklave™</b>	10" x 19" (254 x 475)	6gal/23L	21.5"x20"x14.4" (545x510x365)	3 full/3 half	16.3"x6.7"x0.8" (415x170x20)	4	Cold: 21 mins Hot: 11 mins	230V 50/60	2200W 10A	95 (43)

NOTE: cycle times are approximate and may vary depending on instrument loads. \*\*standard full size cassette is 8" x 11" and standard half size cassette is 8" x 5.5".

## 3870EA Fully Automatic Sterilizer

Our largest automatic tabletop autoclave. Features a closed door active drying system. Perfect for multi-doctor practices, clinics or surgery centers. 15" x 30" chamber accommodates longer instruments or a large number of small instruments. 2 year parts and labor warranty and 10 year chamber warranty

Optional Printer



Supplied with a 3 shelf stand (30"Wx36"Hx34"H)



Item No.	Chamber Dimensions Ø x L in(mm)	Vol	Overall Dimensions DxWxH in(mm)	Tray Dimensions DxWxH in(mm)	No. of Trays	Standard Unwrapped Cycle Time	Voltage(V) Freq.(Hz) *	Power(W) Current(A)	Shipping Weight lbs(kg)
<b>3870EA with stand</b>	15" x 30" (384 x 760)	22gal/85L	34.5"x26"x20.6" (875x665x525)	26.6"x11.3"x1" (675x286x25) 26.6"x13.8"x1" (675x350x25)	2	Cold: 32 mins Hot: 23 mins	230V 50/60	3000W 13.6A	278 (126) including stand

NOTE: cycle times are approximate and may vary depending on instrument loads. \*Model 3870EA requires a voltage between 220V and 235V for proper operation. When applicable a buck/boost transformer (0.5KVA) may be required.

# 2340M, 2540M, 2540MK Manual Sterilizers

Tuttnauer manual autoclaves will compliment any healthcare facility and satisfy all of your sterilization needs. The bright, new, easy to use panel was designed with the operator in mind. Time tested reliability and durability are built into every Tuttnauer product.



## Features:

- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished Stainless Steel chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.
- 1 year parts and labor warranty. 10 year chamber warranty



- 1 Pressure Gauge
- 2 Timer
- 3 Thermostat
- 4 Function Selector

## M - Manual Series

Item No.	Chamber Dimensions Ø x L in(mm)	Vol	Overall Dimensions DxWxH in(mm)	Standard Cassette Capacity**	Tray Dimensions DxWxH in(mm)	No. of Trays	Standard Unwrapped Cycle Time	Voltage(V) Freq.(Hz)	Power(W) Current(A)	Shipping Weight lbs(kg)
2340M	9" x 18" (230 x 470)	5gal/ 19L	21.5"x20"x14.4" (545x510x365)	2 full & 2 half	16.3"x 6.7"x0.8" (415x170x20)	3	Cold: 27 mins Hot: 13 mins	120V 50/60	1400W 12A	85 (39)
2540M	10" x 19" (254 x 475)	6gal/ 23L	21.5"x20"x14.4" (545x510x365)	3 full & 3 half	16.3"x 6.7"x0.8" (415x170x20)	4	Cold: 30 mins Hot: 14 mins	120V 50/60	1400W 12A	85 (39)

## MK - Manual Kwiklave™ Series

2540MK	10" x 19" (254 x 475)	6gal/ 23L	21.5"x20"x14.4" (545x510x365)	3 full & 3 half	16.3"x 6.7"x0.8" (415x170x20)	4	Cold: 21 min Hot: 11 min	230V 50/60*	2200W 10A	85 (39)
--------	--------------------------	--------------	----------------------------------	--------------------	----------------------------------	---	-----------------------------	----------------	--------------	------------

NOTE: cycle times are approximate and may vary depending on instrument loads. \*\*Standard full size cassette is 8" x 11" and standard half size cassette is 8" x 5.5".

The Tuttnauer M Series is also available in a quick cycle model, the Kwiklave (MK). This sterilizer offers all the proven, dependable features of our manual autoclave, with the added benefit of reducing the total heat up time. This autoclave is the perfect choice for quick instrument turnaround or a high volume office. Speed and reliability are accomplished without sacrificing load size. 1 year parts and labor warranty.

**Model 2540MK requires a voltage between 220V and 235V for proper operation. When applicable a buck/boost transformer (0.5KVA) may be required\***



## 3870M Manual Sterilizer

### Large Capacity Manual Autoclave

Our largest manual tabletop autoclave. Perfect for multi-doctor practices, clinics or surgery centers. 15" x 30" chamber accommodates longer instruments or a large number of small instruments. 1 year parts and labor warranty.

Supplied with a 3 shelf stand (30"Wx36"Hx34"H)

**\*Model 3870EA requires a voltage between 220V and 235V for proper operation. When applicable a buck/boost transformer (0.5KVA) may be required.**



### Features:

- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished Stainless Steel chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.
- 1 year parts and labor warranty. 10 year chamber warranty.

Item No.	Chamber Dimensions Ø x L in(mm)	Vol	Overall Dimensions DxWxH in(mm)	Tray Dimensions DxWxH in(mm)	No. of Trays	Standard Unwrapped Cycle Time	Voltage(V) Freq.(Hz)*	Power(W) Current(A)	Shipping Weight lbs(kg)
<b>3870M with stand</b>	15" x 30" (384 x 760)	22gal/ 85L	34.5"x26"x20.6" (875x665x525)	26.6"x11.3"x1" (675x286x25) 26.6"x13.8"x1" (675x350x25)	2	Cold: 32 mins Hot: 23 mins	230V 50/60	3000W 13.6A	278 (126) including stand

NOTE: cycle times are approximate and may vary depending on instrument loads.

## Valueklave™ 1730

The Valueklave1730 will satisfy all of your basic sterilization needs at an economical price. High speed and reliability are built into every Valueklave1730.

### Features:

- Fast Cycle Time. 11 minutes from a hot start\* (Standard Unwrapped Cycle Time).
- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished Stainless Steel chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.



- Dual safety thermostat to protect against overheating.
- International certifications.
- 1 year parts and labor warranty

\*Come up time, sterilization exposure and exhaust.

Item No.	Chamber Dimensions Ø x L in(mm)	Vol	Overall Dimensions DxWxH in(mm)	Standard Cassette Capacity**	Tray Dimensions DxWxH in(mm)	No. of Trays	Standard Unwrapped Cycle Time	Voltage(V) Freq.(Hz)	Power(W) Current(A)	Shipping Weight lbs(kg)
<b>Valueklave 1730M</b>	7" x 13" (170 x 340)	2gal/ 7.5L	17.9"x17.4"x12" (455x440x305)	2 half	11.6"x4.7"x0.8" (295x120x20)	3	Cold: 16 mins Hot: 11 mins	120V 50/60	1350W 11A	55 (25)

NOTE: cycle times are approximate and may vary depending on instrument loads. \*\*Standard half size cassette is 8" x 5.5".

# Elara11™ Pre/Post - Vacuum Class B Sterilizer

## Clean & Waste Water Reservoirs

Reduces cleaning and maintenance on the machine and provides clean steam for every cycle



## EZFill front water filling

Accessible front or top water filling options

## Waste reservoir continuous drain (rear located)

Eliminate the need to manually drain the waste reservoir

## EZView multi-color display

For easy reading, even from a distance

Temp	273.2 °F	Temperature	106.3 °F
Soak Time	4.0 min	Pressure	00.0 °F
Dry Time	20 min	Temperature	28.99 °F
System Ready			

## Network port (rear located)

For connection to a local network to provide remote monitoring of the system

## Comprehensive warranty

1 year parts and labor,  
10 year chamber

## Designed for continuous Operation

Steam is continuously provided by an independent on board steam generator. With the Elara 11, there is no waiting time between cycles

## EZGlide self locking door

Ergonomically friendly EZGlide door features effortless opening and closing with an automatic double safety locking mechanism. Glide the door closed with a gentle push to close and lock it.





## Closed door drying and pre-vacuum air removal

A high volume vacuum pump provides optimum sterilization results and efficient closed door drying. Keeping the door closed throughout the dry cycle maintains sterility and ensures efficient drying. The High-Volume, vacuum pump is very effective at removing moisture from instruments.

## Class B Sterilization Cycles

Pre-vacuum phase efficiently removes air, resulting in the full penetration of steam into wrapped, porous and hollow loads. The post-vacuum drying phase ensures complete drying of wrapped porous loads and hollow instruments. This guarantees that even the most difficult loads will easily reach Sterility Assurance Level (SAL).

The Elara11 offers 4 FDA cleared sterilization programs and 2 test programs, which are the Vacuum Test and the Bowie Dick Test. (Custom cycles for special loads can be created)

Sterilization & Test Programs		Temp.	Sterilization Time	Dry Time	Total Cycle Time Cold Start	Total Cycle Time Hot Start
Description	Icon					
Unwrapped Instruments		273°F (134°C)	4 Minutes	1 Minute	25 Minutes	18 Minutes
Wrapped Instruments		273°F (134°C)	4 Minutes	20 Minutes	59 Minutes	53 Minutes
Unwrapped Delicate Instruments		250°F (121°C)	20 Minutes	1 Minute	40 Minutes	32 Minutes
Wrapped Delicate Instruments		250°F (121°C)	20 Minutes	20 Minutes	72 Minutes	65 Minutes
Vacuum Test	N/A	pre-set				
Bowie & Dick	N/A	273°F (134°C)	3.5 Minutes	2 Minutes	N/A	N/A



Loaded vertically with 4 full and 4 half cassettes (cassette rack included)



Loaded with 5 stainless steel trays

# Elara11™ Pre/Post - Vacuum Class B Sterilizer



## Innovative EZView multi-color display

A bright, new LCD panel uses active multi-color display technology for easy reading, even from a distance

## EZPad

Consists of 3 keys, allowing the user to browse with ease through the sterilization programs and user directories

## Printer

Equipped with a conveniently located printer which documents detailed history of each cycle

## \*USB Port (located under printer door cover)

Store and transfer approximately 100 cycles of data

\*Includes USB flash drive with machine.

## Innovative multi-color display

Real time information is easy to read, even from a distance.

Indicates program icon and name, cycle parameters, temperature and pressure in the chamber.

During the selected program each stage of the sterilization cycle is displayed with both an active color wheel and text.

- The color wheel and text change for each phase of the cycle
- Wheel rotates to indicate activity through each part of the cycle
- Remaining time displayed during Water Filling, Sterilization, and Drying phases
- Display available in multiple languages



## Technical Specifications

Model	Chamber Dimensions OxL in (mm)	Volume	Overall Dimensions* DxWxH in (mm)	Standard cassette capacity**	Tray Dimensions DxWxH in (mm)	No. of Trays	Voltage*** (V) Freq. (Hz)	Power (W) Current (A)	Shipping Weight lbs (kg)
<b>Elara11</b>	11"x19.8" (280x504)	7.5 gal. 28.5L	26"x20.9"x17.3" (660x530x440)	4 Full & 4 Half** (loaded vertically)	16.3"x6.7"x0.6" ( 442x173x19)	5	230V 50/60	2300W 10A	171 (78)

\* Minimum tabletop depth of 24"


\*\* Standard full size cassette is 8"x11" and standard half size cassette is 8"x5.5"

\*\*\* Requires a voltage between 220V and 235V for proper operation. Voltage outside this area will require a buck/boost transformer (0.5KVA).

## R.PC.R Software (Optional)

(Remote PC Reporting Software)

- Remote monitoring of multiple autoclaves from any PC on your local network in real time
- Automatic downloading of cycle history to your PC
- Built in memory capable of storing approximately 100 cycles of data
- Easy management of each machines cycle history
- Analysis of any cycle process using easy to understand graphs or table data
- Generate PDFs from cycle analysis that can easily be printed for future reference
- R.PC.R can also analyze and store cycle history downloaded with a USB drive



## Standards and Directives

The Elara11 meets established International standards and specifications:

**USA Standards:** ANSI/ AAMI ST55, ASME Sec. VIII, UL 61010A-1, UL 61010A-2-041, FDA 510(K) Cleared, ISO 17665-1. The Quality System complies with ISO 13485:2003 and ISO 9001:2008

**Canada Standards:** CRN, CSA

**EU Standards:** EN 13060:2004, EN 13445, EN 61010-1, EN 61010-2-041, EN 61010-2-040, EN 554 EN 61326 EN 61326. Complying with MDD 93/42, PED 97/23, RoHS & WEEE Directives



# Clean & Simple™ Ultrasonic Cleaning Systems



Tuttnauer's Clean & Simple Ultrasonic Cleaning Systems are manufactured with only the highest quality components. The machines provide 60 kHz of quiet cleaning power which is less aggressive to instruments while still removing all surface contamination. The contemporary design and quiet operation compliment any office environment. Clean & Simple Ultrasonic Systems are available in 2 sizes and with a full selection of accessories to meet your specific needs. The 1 gallon holds a standard selection of instruments or 2 half size cassettes. The 3 gallon holds 3 full size cassettes.

System Specifications	Tank Dimension (Inches(Cms)	External Dimension Inches(Cms)	Tank Capacity Gallons (Liters)
<b>CSU1</b>	9.38 (23.83) W 4.0 (10.16) H 5.38 (13.67) D	10.25 (26.03) W 8.25 (20.95) H 6.5 (16.51) D	0.85 (3.2)
<b>CSU3</b>	15.5 (39.37) W 6.0 (15.24) H 9.0 (22.86) D	16.5 (41.91) W 12.13 (30.81) H 10.0 (25.4) D	3.25 (12.3)



## Ultrasonic Cleaning Tablets

Clean & Simple is an ultrasonic / enzymatic solution dispensed in a unique tablet form. Drop 2 tablets into your ultrasonic tank already filled with tap water and the tablets will dissolve in about a minute. This is a non-ionic solution which is non-corrosive, non-toxic, biodegradable and non-caustic. Available in boxes of 64 tablets, Item No. CS0064 and 144 tablets, Item No. CS0144.

### Features:

- Easy to use tablet form
- Eliminates handling of heavy 1 gallon containers
- No bulky storage
- No pre-mixing required
- Enzymatic solution effectively breaks down protein



## Chamber Brite™

One of the most effective and easy to use autoclave cleaners. Chamber Brite effectively cleans and descales the chamber, reservoir, and tubing of most steam autoclaves. Available 10 per box. Item No. CB0010.


### Features:

- Pre-measured packs.
- No pre-mixing required.
- Usage promotes efficiency.
- Odor free.
- Easy storage.



## Instrument Pouch Rack

All pouched instruments should be placed in a rack for proper sterilization and drying. Our stainless steel pouch rack is convenient for the loading and unloading of bagged instruments. (Two racks per box. Item No. AR910 for all 9" and 10" chambers. Item No. AR920 for all 15" chambers).



## Water Distiller

Tuttnauer offers a distiller that provides pure water. Water that is 99% free of total dissolved solids. Eliminates the inconvenience and expense of buying bottled water.

Its ease of operation makes it ideal for any medical, dental or laboratory application. UL listed.

Available in 4 models:

- Cat. No. 9000 (1 gal. System)
- Cat. No. 7000\* (3.5 gal. System)
- Cat. No. 7000-8\* (8 gal. System)
- Cat. No. 7000-12\* (12 gal. System)

Series 7000\* is directly connected to the water supply for continuous operation.



Model 7000



Model 9000

# Your Sterilization & Infection Control Partners



## Company Profile

For over 90 years, Tuttnauer's sterilization and infection control products have been trusted by hospitals, universities, research institutes, clinics and laboratories throughout the world. Supplying a range of top-quality products to over 100 countries, Tuttnauer has earned global recognition as a leader in sterilization and infection control.

“Our position as market shapers is based on years of experience and technology leadership, but our true pride comes from the strong bond of trust we create with our customers, building a mutually successful future.”  
Ran Tuttnauer, CO



Fully automatic Series



Manual M series



Valueklave 1730



Elara11

All Tuttnauer autoclaves comply with the strictest international directives and standards: AAMI/ANSI ST-55, ASME, UL 61010-1+61010-2-041 UL file E206879, FDA cleared.

## Autoclaves & Accessories for Healthcare Professionals

Tuttnauer USA Co., Ltd.  
25 Power Drive  
Hauppauge, NY 11788  
Tel: +800 624 5836, +631 737 4850 Fax: +631 737 0720  
E-mail: [info@tuttnauerUSA.com](mailto:info@tuttnauerUSA.com), [www.tuttnauerUSA.com](http://www.tuttnauerUSA.com)

Tuttnauer Europe b.v.  
Hoeksteen 11, 4815 PR  
P.O.B. 7191, 4800 GD Breda  
The Netherlands  
Tel: +31 (0) 765 423 510 Fax: +31 (0) 765 423 540  
E-mail: [info@tuttnauer.nl](mailto:info@tuttnauer.nl)

Tuttnauer, EZ11Plus, EZ9Plus, EZ9, EZ10, EZ10k, Kwiklave, Valueklave, Elara11, Chamber Brite and Clean & Simple are registered trademarks of the Tuttnauer USA Co

Distributed by:

