

PANEL

Screen Size	49"
Resolution	1,920 x 1,080 (FHD)
Brightness(Typ.,cd/m ²)	450

CONNECTIVITY

Input	HDMI, DP, DVI-D, RGB, Audio, USB 2.0
Output	DP, Audio
External Control	RS232C In/out, RJ45 (LAN) In, IR In

MECHANICAL SPECIFICATIONS

Bezel Width	2.25 mm (T/L), 1.25 mm (B/R)
Dimension (Monitor) (W x H x D)	1,077.6 x 607.8 x 89.7mm
Weight (Head)	17.8kg
Dimensions (Carton) (W x H x D)	1,214 x 778 x 263mm
Packed Weight	22.8kg
VESA™ Standard Mount Interface	600 x 400 mm

ENVIRONMENTAL CONDITIONS

Operation Temperature	0 °C to 40 °C
Operation Humidity	10% to 80%

POWER

Power Supply	100 -240V~, 50/60Hz
--------------	---------------------

Power Type	Built-In Power
------------	----------------

POWER CONSUMPTION

Typ.	90 W
------	------

Max	110 W
-----	-------

Smart Energy Saving	55 W
---------------------	------

CERTIFICATIONS

Safety	CB / NRTL
--------	-----------

EMC	FCC Class "A" / CE / KC
-----	-------------------------

ErP	Yes (EU Only)
-----	---------------

MEDIA PLAYER COMPATIBILITY

OPS Type Compatible	No
---------------------	----

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
-----------------------------	---------------

Control and Monitoring Software	SuperSign Control/Control+
---------------------------------	----------------------------

ACCESSORIES

Basic

Remote Controller, Power Cord, RS232C Cable, LAN Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual

Optional

Wall mount (Landscape: WM-L640V, Portrait: WM-P640V)
