

PANEL

Screen Size	55"
Resolution	1,920 x 1,080 (FHD)
Brightness(Typ.,cd/m ²)	500
Dynamic CR	500,000 : 1 (The luminosity ratio of Full Black/Full White color on video input condition.)
Life Time (Typ.)	60,000 Hrs

CONNECTIVITY

Input	HDMI (2), DP, DVI-D, Audio, USB
Output	DP, Audio
External Control	RS232C In/out, RJ45 (LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	2.25 mm (T/L) / 1.25 mm (B/R)
Monitor Dimension (W x H x D)	1,213.4 x 684.2 x 93.1 mm
Weight (Head)	20.3kg
Carton Dimensions (W x H x D)	1,353 x 980 x 263 mm
Packed Weight	33kg
Handle	Yes

VESA™ Standard Mount Interface	600 x 400 mm
--------------------------------	--------------

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
-----------------------	-------------

Operation Humidity	10% to 80%
--------------------	------------

POWER

Power Supply	100-240V~, 50/60Hz
--------------	--------------------

Power Type	Built-In Power
------------	----------------

POWER CONSUMPTION

Typ. / Max.	130W/150W
-------------	-----------

Smart Energy Saving	62W
---------------------	-----

CERTIFICATION

Safety	CB / NRTL
--------	-----------

EMC	FCC Class "A"/CE/KC
-----	---------------------

ErP	Yes (EU Only)
-----	---------------

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
-----------------------------	---------------

Control and Monitoring Software	SuperSign Control/Control+
---------------------------------	----------------------------

ACCESSORY

Basic

Remote Controller, Power Cord, RS232C Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual

Optional

Wall Mount (Landscape: WM-L640V, Portrait: WM-P640V)
