

PANEL

Screen Size	75" Class
Native Resolution	3,840 x 2,160 (UHD), M+
Brightness(Typ., with Protective Glass, cd/m ²)	3000

CONNECTIVITY

Input	HDMI, DP, DVI-D, Audio In, USB 3.0, SD Card
Output	DP, External Speaker (*waterproof speakers are mandatory for outdoor installation)
External Control	RS232C In/out, RJ45 In

PHYSICAL SPECIFICATION

Bezel Width	110mm(T), 230mm(B), 73.3mm(L/R)
Monitor Dimension (W x H x D)	1,075.6 x 1,991.6 x 218.9 mm
Weight (Head)	180 kg

ENVIRONMENT CONDITIONS

Operation Temperature	-30 °C to 50 °C
Operation Humidity	5 % to 100 %

POWER

Power Supply	100-240V~, 50/60Hz
--------------	--------------------

Power Type	Built-In Power
-------------------	----------------

POWER CONSUMPTION

Typ. / Max.	700 W / 1000 W
--------------------	----------------

Smart Energy Saving	350 W
----------------------------	-------

STANDARD(CERTIFICATION)

Safety	UL / cUL / CB
---------------	---------------

EMC	FCC Class "A" / CE / KC
------------	-------------------------

ErP / Energy Star	Yes (EU Only) / No
--------------------------	--------------------

MEDIA PLAYER COMPATIBILITY

OPS type compatible	No
----------------------------	----

External Media player Attachable	Yes (Available space for media player installation inside the product)
---	--

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign CMS
------------------------------------	---------------

Control and Monitoring Software	SuperSign C
--	-------------

ACCESSORY

Basic	Remote Controller, Manual, QSG, Regulation Book, Phone to RS232C Gender, USB cable, HDMI cable
--------------	--

Optional	Enclosure Stand (ST-750X)
-----------------	---------------------------

