

Shoulder Measurement



THIS MEASURES THE BROADNESS
OF A PERSON'S SHOULDERS.
MEASURE FROM SHOULDER BONE
TO SHOULDER BONE.

MAKING SURE YOU ARE STANDING UP STRAIGHT IN PERFECT POSTURE STANCE BEFORE TAKING YOUR MEASUREMENT. HAVING AN AGGRESSIVE SHOULDER ANGLE OR SHOULDER SLANT CAN POTENTIALLY GIVE YOU A GREATER MEASUREMENT MAKING IT TOO BIG!



Chest Measurement



MEASURED AROUND THE THICKEST PART OF THE CHEST AND BACK, WITH THE MEASURING TAPE HELP SNUG (NOT TOO TIGHT) TO THE SKIN.

CIRCUMFERENCE AT NIPPLE
HEIGHT. LET THEM BREATHE IN,
OUT AND INTO A RELAXED STATE.
MAKE SURE THE MEASURING TAPE
IS LEVEL ALL THE WAY AROUND.
ANY DEVIATION WILL ALTER YOUR
MEASUREMENTS.



Stomach Measurement



MEASURED AT THE NARROWEST
POINT OF THE WAIST (ROUGHLY
AROUND THE HEIGHT OF THE
JACKET BUTTON). THIS IS
GENERALLY HALF WAY BETWEEN
YOUR NIPPLE AND BELLY BUTTON.

WE FIND THIS TO BETHE MOST ACCURATE METHOD.



Sleeve Measurement



MEASURED FROM THE BONE POINT ON SHOULDER, TO WHERE THE PREFERRED SLEEVE WILL END.

JACKET SLEEVE WILL BE 1-1.5CM SHORTER THAN SHIRT SLEEVE USING THE SAME MEASUREMENT.



Front Jacket Measurement



MEASURING FROM THE TOP
(WHERE YOUR TRAP MUSCLE
MEETS YOUR NECK). WITH HANDS
RELAXED BY YOUR SIDE, YOU
SHOULD BE MEASURING DOWN
BETWEEN THE WRIST OR FIRST
THUMB KNUCKLE. NOTE: YOU
SHOULD NOT BE MEASURING
BELOW THE BUTTOCKS OR
CROTCH.

AS A GENERAL RULE THE BACK JACKET SHOULD BE AROUND 2-4CM SHORTER THAN THE FRONT JACKET LENGTH.



Back Jacket Measurement



MEASURE FROM THE TOP BONE OF THE BACK OF THE NECK (USUALLY THE BONE THAT PROTRUDES THE MOST, RIGHT UNDER YOUR SHIRT COLLAR) TO JUST ABOVE THE TAILBONE. NOTE: THIS SHOULD END A FEW CENTIMETRES BELOW THE TROUSER WAISTBAND – AS SHOWN IN IMAGE.



Bicep Measurement



MEASURED AROUND THE THICKEST PART OF THE BICEP, WHICH TENDS TO BE THE MIDDLE OF THE BICEP. IF YOU MEASURE TOO HIGH ON THE ARM, IT WILL INCLUDE TOO MUCH TRICEP WHICH IN TURN WILL GIVE YOU A BIGGER MEASUREMENT.



Seat Measurement





ENSURE EVERYTHING IS OUT OF YOUR POCKETS. MEASURE AROUND THE THICKEST PART OF THE BOTTOM. TAKE MULTIPLE MEASUREMENTS AT DIFFERENT HEIGHTS AND GO WITH THE BIGGEST MEASUREMENT.

AS A GENERAL RULE WITH NORMAL SHAPED BUTTOCK'S, YOU MEASURE THE THICKEST PART.



Waist Measurement



THIS IS THE HEIGHT AT WHICH
THE TROUSER SHOULD SIT
COMFORTABLY. IF YOU ARE
WEARING JEANS OR CASUAL
PANTS, YOU SHOULD TAKE YOUR
MEASUREMENT SLIGHTLY HIGHER
AS A SUIT TROUSER SHOULD SIT
ON THE WAIST INSTEAD OF THE
HIP.



Thigh Measurement



MEASURE AROUND THE THICKEST PART OF YOUR THIGH, USUALLY HIGHER UP.



Knee Measurement



MEASURED ACROSS THE KNEECAP.
SHOULD BE ROUGHLY AROUND THE
SAME AS THE CIRCUMFERENCE OF THE
THICKEST PART OF THE CALVES. PUT
DOWN WHICH EVER MEASUREMENT IS
BIGGER OF THE TWO.



Ankle Measurement



MEASURED AROUND THE ANKLE BONE, NORMALLY RANGING BETWEEN 26 TO 28CM. UNLESS THEY ARE AN OLDER GENTLEMAN OR SLIGHTLY LARGER, DON'T GO OVER 28CM. 25CM IF THEY YOU SLIM AND WANT A NICE TAPERED ANKLE, AS THE ALLOWANCE SHOULD ALLOW ENOUGH ROOM. BE WARY OF THUNDER CALVES.



Crotch Measurement





MEASURED FROM THE TOP OF THE TROUSER WAISTBAND, AROUND TO THE TOP OF THE BACK OF THE TROUSER WAISTBAND. MAKE SURE THE MEASURING TAPE IS HUGGING THE BODY WITHOUT IT BEING TOO TIGHT OR RESTRICTIVE.

NOTE: BEFORE MEASURING YOUR CROTCH, PULL YOUR PANTS RIGHT UP TO THE POINT OF DISCOMFORT. THEN LET IT DROP SLIGHTLY TO ASSIST IN PROVIDING A ACCURATE MEASUREMENT.



Outseam Measurement



STARTING POINT SHOULD BE WHERE YOU MEASURED YOUR WAIST (AS SHOWN IN THE IMAGE PROVIDED).

MEASURE DOWN TO JUST BELOW YOUR ANKLE KNUCKLE. THIS WILL DETERMINE THE LENGTH OF YOUR TROUSER.

