

Waist Measurement



THIS IS THE HEIGHT AT WHICH
THE TROUSER SHOULD SIT
COMFORTABLY. IF YOU ARE
WEARING JEANS OR CASUAL
PANTS, YOU SHOULD TAKE YOUR
MEASUREMENT SLIGHTLY HIGHER
AS A SUIT TROUSER SHOULD SIT
ON THE WAIST INSTEAD OF THE
HIP.



Seat Measurement





ENSURE EVERYTHING IS OUT OF YOUR POCKETS. MEASURE AROUND THE THICKEST PART OF THE BOTTOM. TAKE MULTIPLE MEASUREMENTS AT DIFFERENT HEIGHTS AND GO WITH THE BIGGEST MEASUREMENT.

AS A GENERAL RULE WITH NORMAL SHAPED BUTTOCK'S, YOU MEASURE THE THICKEST PART.



Thigh Measurement



MEASURE AROUND THE THICKEST PART OF YOUR THIGH, USUALLY HIGHER UP.



Knee Measurement



MEASURED ACROSS THE KNEECAP.
SHOULD BE ROUGHLY AROUND THE
SAME AS THE CIRCUMFERENCE OF THE
THICKEST PART OF THE CALVES. PUT
DOWN WHICH EVER MEASUREMENT IS
BIGGER OF THE TWO.



Ankle Measurement



MEASURED AROUND THE ANKLE BONE, NORMALLY RANGING BETWEEN 26 TO 28CM. UNLESS THEY ARE AN OLDER GENTLEMAN OR SLIGHTLY LARGER, DON'T GO OVER 28CM. 25CM IF THEY YOU SLIM AND WANT A NICE TAPERED ANKLE, AS THE ALLOWANCE SHOULD ALLOW ENOUGH ROOM. BE WARY OF THUNDER CALVES.



Crotch Measurement





MEASURED FROM THE TOP OF THE TROUSER WAISTBAND, AROUND TO THE TOP OF THE BACK OF THE TROUSER WAISTBAND. MAKE SURE THE MEASURING TAPE IS HUGGING THE BODY WITHOUT IT BEING TOO TIGHT OR RESTRICTIVE.

NOTE: BEFORE MEASURING YOUR CROTCH, PULL YOUR PANTS RIGHT UP TO THE POINT OF DISCOMFORT. THEN LET IT DROP SLIGHTLY TO ASSIST IN PROVIDING A ACCURATE MEASUREMENT.



Outseam Measurement



STARTING POINT SHOULD BE WHERE YOU MEASURED YOUR WAIST (AS SHOWN IN THE IMAGE PROVIDED).

MEASURE DOWN TO JUST BELOW YOUR ANKLE KNUCKLE. THIS WILL DETERMINE THE LENGTH OF YOUR TROUSER.

