-J03629 2008-07-25

OIL COOLER KIT

GENERAL

Kit Number

Q1002.1AM

Models

For the most up-to-date model fitment information, see product label or www.buell.com (English only).

Additional Parts Required

A WARNING

The rider's safety depends upon the correct installation of this kit. Use the appropriate service manual procedures. If the procedure is not within your capabilities or you do not have the correct tools, have a Buell dealer perform the installation. Improper installation of this kit could result in death or serious injury. (00334a)

NOTE

This instruction sheet references service manual information. A service manual for your model motorcycle is required for this installation and is available from a Buell dealer.

Kit Contents

See Figure 1 and Table 1.

REMOVAL

A WARNING

To prevent accidental vehicle start-up, which could cause death or serious injury, disconnect negative (-) battery cable before proceeding. (00048a)

- Disconnect negative (-) battery cable following the procedure in the service manual.
- 2. Remove the oil cooler following the instructions in the service manual. Discard the 1/4-20 crossover hose clamp nut. Save all other hardware for installation.

INSTALLATION

- See Figure 1. Install the new oil cooler (1) following the instructions in the service manual.
- 2. Install the M6 clamp nut (2).
- Install the previously removed components following the instructions in the service manual.
- 4. Connect the negative (-) battery cable.

SERVICE PARTS




Figure 1. Service Parts: Oil Cooler Kit

Table 1. Service Parts

| Item | Description (Quantity) | Part Number |
|------|------------------------|---------------------|
| 1 | Oil cooler assembly | Not Sold Separately |
| 2 | Nut, M6 | D0600.2CBL |