

INSTRUCTION SHEET

Buell
AMERICAN MOTORCYCLES

-J01869

Kit Number 43686-01Y

REV. 4-20-00

Rear Axle Cover Kit

General

Pegasus axle nut kits are designed for all 1995 and later Buell model motorcycles, except Buell Blast.

Kit contents:

QTY	DESCRIPTION	PART NO.
1	Axle nut cover, RH	Not Sold
1	Axle nut cover, LH	Not Sold
1	Pegasus medallion, RH	
1	Pegasus medallion, LH	
2	Set screw, 1/4-20 x 3/8"	Not Sold
1	Hex drive wrench., 1/8"	Not Sold

NOTE

Install both axle nut covers on the appropriate axle before installing the Pegasus medallion. The left and right covers have different internal dimensions. If the cover does not fit one side, install it on the other side of the motorcycle

Installation

1. Install the covers on the appropriate axle with the set screw provided positioned on the bottom. If a cover is being installed over a hex nut, position the cover so that the set screw makes contact with a flat portion of the the hex nut. Securely tighten the set screw with the supplied hex drive wrench.
2. The surface of the axle cover should be clean and free of oil or grease.
3. Remove the backing off of the Pegasus medallion.
4. Carefully position the Pegasus medallion in the counterbore portion of the axle nut so that the Pegasus is level and pointing to the front of the motorcycle. Press firmly into place.

INSTRUCTION SHEET

Buell
AMERICAN MOTORCYCLES

-J01869

Kit Number 43686-01Y

REV. 4-20-00

Rear Axle Cover Kit

General

Pegasus axle nut kits are designed for all 1995 and later Buell model motorcycles, except Buell Blast.

Kit contents:

QTY	DESCRIPTION	PART NO.
1	Axle nut cover, RH	Not Sold
1	Axle nut cover, LH	Not Sold
1	Pegasus medallion, RH	
1	Pegasus medallion, LH	
2	Set screw, 1/4-20 x 3/8"	Not Sold
1	Hex drive wrench., 1/8"	Not Sold

NOTE

Install both axle nut covers on the appropriate axle before installing the Pegasus medallion. The left and right covers have different internal dimensions. If the cover does not fit one side, install it on the other side of the motorcycle

Installation

1. Install the covers on the appropriate axle with the set screw provided positioned on the bottom. If a cover is being installed over a hex nut, position the cover so that the set screw makes contact with a flat portion of the the hex nut. Securely tighten the set screw with the supplied hex drive wrench.
2. The surface of the axle cover should be clean and free of oil or grease.
3. Remove the backing off of the Pegasus medallion.
4. Carefully position the Pegasus medallion in the counterbore portion of the axle nut so that the Pegasus is level and pointing to the front of the motorcycle. Press firmly into place.