

Recommended Application

Make certain that your wood surface is free from all dirt, stains, oil, grease, grime, mildew, fungus or loose bark prior to finish application. LOG GUARD® Interior Clear Wood Finish may be applied by brush, airless sprayer or pump sprayer. If spray application is used then back brushing is necessary. If a color coat is desired, we recommend applying UV GUARD® Wood Finish or UV GUARD® II Wood Finish prior to the LOG GUARD® Interior Clear Wood Finish. If a stain is applied then it is best to wait 24 hours before applying your first coat of LOG GUARD® Interior Clear Wood Finish. LOG GUARD® Interior Clear Wood Finish will be dry to the touch in 30 minutes to 1 hour and ready for a light sand after 4 hours depending on temperature and relative humidity. Sanding between coats is highly recommended. Make sure that all dust is removed from the wood surface prior to application of LOG GUARD® Interior Clear Wood Finish and between subsequent coats. Do not use LOG GUARD® Interior Clear Wood Finish over deteriorated finishes. 2-3 finish coats of LOG GUARD® Interior Clear Wood Finish is recommended for a smooth and even finish. Please inquire with us for more details or questions about applying LOG GUARD® Interior Clear Wood Finish on your next project.

Maintenance

No upkeep is required.

Packaging

Sample Jar, 1 Gallon Pail and 5 Gallon Pail

Coverage Rates

150-300 square feet per gallon on the first coat.
300-500 square feet per gallon on subsequent coats.

**The above coverage rates are highly dependent upon the porosity of the wood and the condition of the existing stain. Do not thin or dilute product.

Experience & Reputation

For over 30 years, the Weatherall Company has been making and delivering the best wood finishes, chinking and caulking products in the industry. ***Some things need to be earned.***

Complete Wood Care System

We are proud to offer wood finishes, chinking and caulking products designed specifically for logs, wood siding or timbers. We believe that our system of products will not only enhance the beauty of your home, but also offer unsurpassed protection and longevity. ***Let us take the worry out of compatibility issues.***

We are making it easy to GO GREEN.

In a world that moves at lightning speed it is sometimes easy to forget about being socially responsible. The Weatherall Company offers a full line of environmentally friendly products that protect you, the environment and your wood structure. No longer do you need to breathe harsh chemicals to get the results that you desire. ***Mother Nature would like to take this opportunity to thank you.***

WE CARE Attitude

Whether you are looking to purchase more materials or simply need advice, our goal is to make sure that you get the best customer experience. ***Let us show you that CUSTOMERS do matter.***

Try Before You Buy

You've waited this long to get your dream house; why not wait a couple more days to make sure you get the colors you want? We will send you a kit that includes stain samples, caulking color charts, chinking color charts and application guides. ***Knowing exactly what you want is a good thing.***



LOG GUARD® INTERIOR

CLEAR WOOD FINISH

Waterborne Interior Top Coat



LOG • TIMBER • SIDING • PANELING

Add Beauty, Protection and Depth to Your Wood



The Clear Choice For Interior Wood

LOG GUARD® INTERIOR

CLEAR WOOD FINISH

Add Beauty, Protection, and Depth to Your Wood

LOG GUARD® Interior Clear Wood Finish protects interior wood surfaces with a tough, durable, urethane-like finish that enhances the beauty of wood. Strong odors are a thing of the past. LOG GUARD® Interior Clear Wood Finish is a water-based environmentally friendly, crystal clear coating that has an extremely low VOC content. LOG GUARD® Interior Clear Wood Finish makes cleaning your wood surfaces easy and helps stop your wood from yellowing over time. There is no better choice to provide beauty, depth and protection to the wood on the inside of your house.

Why it Works

LOG GUARD® Interior Clear Wood Finish creates a hard shell that is resistant to household cleaners and detergents but also offers just enough flexibility to expand and contract with the movement of the wood on the interior of your home.

Physical Properties

Viscosity: 150 cps

Density: 8.5 ± 0.1 lbs./gal.

pH: 8.5 ± 0.5

VOC: 60 g/l

% Solids: 27-28%

Odor: Odorless when dry

Toxicity: Non-toxic

Shelf Life: 2 Years

Test Method: ASTM G-53

Features

- Crystal Clear Finish
- Easy Application
- Non-Yellowing Formula
- Adds Beauty & Depth
- Eco-Friendly
- Flexible yet Scuff Resistant Finish
- Gloss or Satin Sheen
- Compatible with Most Other Finishing Products
- Dries to Urethane like Finish
- Low to No Maintenance
- Water Based Formula
- Soap & Water Clean Up

Application Tips

- Always test a sample on your wood.
- Thoroughly stir contents prior to application. DO NOT SHAKE.
- Tannin stains should be dealt with prior to application.
- Great for logs, cabinets, trim, T&G, paneling and woodwork.
- Not recommended for floors or exteriors.
- Lightly sand between coats.