



# Safety Data Sheet

Issue Date 21-May-2013

Revision Date: 04-Jul-2013

Version 1

## 1. IDENTIFICATION

### Product Identifier

**Product Name** PC - Woody, Part A

### Other means of identification

**SDS #** 130625-17

### Recommended use of the chemical and restrictions on use

**Recommended Use** Adhesives.

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Protective Coatings Co.  
221 S Third St.  
Allentown, PA 18102 USA

### Emergency Telephone Number

**Company Phone Number** 610-432-3543 / 800-220-2103  
**Emergency Telephone (24 hr)** INFOTRAC 1-352-323-3500 (International)  
1-800-535-5053 (North America)

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

### Signal Word

**Warning**

### Hazard Statements

Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction



**Appearance** White paste

**Physical State** Paste

**Odor** Mild

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Contaminated work clothing should not be allowed out of the workplace

**Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Get medical attention if irritation occurs  
 IF ON SKIN: Wash with plenty of soap and water  
 Take off contaminated clothing and wash it before reuse  
 If skin irritation or rash occurs: Get medical advice/attention

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Bisphenol A - Epichlorohydrin polymer	25068-38-6	60-65
Kaolin	1332-58-7	8-10
Hydrous magnesium silicate	14807-96-6	5-7
Wood flour	Proprietary	5-7
Bis(2-ethylhexyl) terephthalate	6422-86-2	4-6
Glycidyl Ethers of Bisphenol F Resin	Proprietary	1-3
Titanium Dioxide	1317-80-2	<1
Polyethylene fiber	Proprietary	<1

Product contains a proprietary mixture of ingredients.

### 4. FIRST-AID MEASURES

**First Aid Measures**

<b>General Advice</b>	Provide this SDS to medical personnel for treatment. After first aid, get appropriate in-plant, paramedic, or community medical support.
<b>Eye Contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation occurs.
<b>Skin Contact</b>	Wash with soap and water. Remove and wash contaminated clothing before reuse. Get medical attention if irritation occurs.
<b>Inhalation</b>	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician / poison center if individual's condition declines or if symptoms persist.
<b>Ingestion</b>	Do not induce vomiting. Clean mouth with water and drink afterwards plenty of water. Seek medical advice.

**Most important symptoms and effects**

**Symptoms** Causes eye irritation. Direct contact may cause temporary redness and discomfort. Causes skin irritation. Can cause respiratory tract irritation. May cause nose, throat, and lung irritation.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Skin and eye conditions may be aggravated by long term exposure. Application of corticosteroid cream has been effective in treating skin irritation.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Dry chemical, CO<sub>2</sub> or water spray.

**Unsuitable Extinguishing Media** Not determined.

**Specific Hazards Arising from the Chemical**

Product is not flammable.

**Hazardous Combustion Products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Aldehydes.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Wear positive pressure self-contained breathing apparatus (SCBA). Do not release runoff from fire control methods to sewers or waterways. NFPA Class IIIB.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Wear protective gloves/protective clothing and eye/face protection. Avoid breathing vapors, mist or gas. Remove any contaminated clothing and wash thoroughly before reuse.

**For Emergency Responders** Follow applicable OSHA regulations (29 CFR 1910.120).

**Environmental Precautions** See Section 12 for additional Ecological Information. Prevent runoff from entering drains, sewers or streams.

**Methods and material for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an absorbent material.

**Methods for Clean-Up** Dispose of contents/container to an approved waste disposal plant. Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on Safe Handling** Handle in accordance with good industrial hygiene and safety practice. Wear appropriate personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash face, hands, and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store contents under <90F (32C) . NFPA Class IIIB storage.

**Incompatible Materials** Strong oxidizing agents, acids, Amines, Bases.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Kaolin 1332-58-7	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Hydrous magnesium silicate 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
Wood flour	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust

**Appropriate engineering controls**

**Engineering Controls** Provide general or local exhaust ventilation if product is sanded or ground.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** Chemical safety goggles/faceshield.

**Skin and Body Protection** Wear protective gloves and protective clothing.

**Respiratory Protection** Ensure adequate ventilation, especially in confined areas. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical State</b>	Paste	<b>Odor</b>	Mild
<b>Appearance</b>	White paste	<b>Odor Threshold</b>	Not determined
<b>Color</b>	White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting Point/Freezing Point	Not available	
Boiling Point/Boiling Range	No data	

<b>Flash Point</b>	248.88 °C / 480 °F	CC (closed cup)
<b>Evaporation Rate</b>	Not determined	
<b>Flammability (Solid, Gas)</b>	Not determined	
<b>Upper Flammability Limits</b>	Not available	
<b>Lower Flammability Limit</b>	Not available	
<b>Vapor Pressure</b>	Not determined	
<b>Vapor Density</b>	Not available	
<b>Specific Gravity</b>	0.79	(1=Water) @ 4°C
<b>Water Solubility</b>	Insoluble in water	
<b>Solubility in other solvents</b>	Alcohols	
<b>Partition Coefficient</b>	Not determined	
<b>Autoignition Temperature</b>	Not determined	
<b>Decomposition Temperature</b>	Not determined	
<b>Kinematic Viscosity</b>	Not determined	
<b>Dynamic Viscosity</b>	Not determined	
<b>Explosive Properties</b>	Not determined	
<b>Oxidizing Properties</b>	Not determined	
<b>Density</b>	6.6 lbs/gal	

## 10. STABILITY AND REACTIVITY

### Reactivity

Not reactive under normal conditions.

### Chemical Stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

**Hazardous Polymerization**      Hazardous polymerization does not occur.

### Conditions to Avoid

Keep out of reach of children.

### Incompatible Materials

Strong oxidizing agents, acids, Amines, Bases.

### Hazardous Decomposition Products

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Product Information**

**Eye Contact**      Causes serious eye irritation.

**Skin Contact**      Causes skin irritation.

**Inhalation**      Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

**Ingestion**      May cause discomfort if swallowed.

### Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol A - Epichlorohydrin polymer 25068-38-6	= 11400 mg/kg ( Rat )	20000 mg/kg (rabbit)	-
Wood flour	> 5 g/kg ( Rat )	> 2 g/kg ( Rabbit )	> 5800 mg/m <sup>3</sup> ( Rat ) 4 h

### Information on physical, chemical and toxicological effects

**Symptoms** Please see section 4 of this SDS for symptoms.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** May cause an allergic skin reaction.

**Carcinogenicity** This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Chemical Name	ACGIH	IARC	NTP	OSHA
Hydrous magnesium silicate 14807-96-6		Group 3		
Polyethylene fiber		Group 3		

*IARC (International Agency for Research on Cancer)  
Group 3 IARC components are "not classifiable as human carcinogens"*

### Numerical measures of toxicity

Not determined

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hydrous magnesium silicate 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static		

### Persistence/Degradability

Not determined

### Bioaccumulation

Not determined

### Mobility

Not determined

### Other Adverse Effects

Not determined

## 13. DISPOSAL CONSIDERATIONS

### Waste Treatment Methods

**Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated Packaging**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

## 14. TRANSPORT INFORMATION

<b>Note</b>	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
<b>DOT</b>	Not regulated
<b>IATA</b>	Not regulated
<b>IMDG</b>	Not regulated

## 15. REGULATORY INFORMATION

**International Inventories**

Not determined

**Legend:**

*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*

*DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*

*EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

*ENCS - Japan Existing and New Chemical Substances*

*IECSC - China Inventory of Existing Chemical Substances*

*KECL - Korean Existing and Evaluated Chemical Substances*

*PICCS - Philippines Inventory of Chemicals and Chemical Substances*

**US Federal Regulations****SARA 313**

Not determined

**US State Regulations****U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Kaolin 1332-58-7	X	X	X
Hydrous magnesium silicate 14807-96-6	X	X	X
Wood flour	X	X	X
Titanium Dioxide 1317-80-2			X

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Instability</b>	<b>Special Hazards</b>
	1	1	0	Not determined
<b>HMIS</b>	<b>Health Hazards</b>	<b>Flammability</b>	<b>Physical Hazards</b>	<b>Personal Protection</b>
	1	1	0	B- Safety Glasses, Gloves

**Issue Date** 21-May-2013  
**Revision Date:** 04-Jul-2013  
**Revision Note** New format

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**